							
1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number	
Sedgwick	NE 1/4	SE 1/4 S	W 1/4	20	т 26 s	R 1E EW	
Distance and direction frem nearest town or city str	eet address of well if loca	ted within city?					
734 W. 46th N. Wichita, KS.							
	N, Earl						
	. 46th N.				Board of Agriculture, Di	tvivsion of Water Resource	
		ال ا		67204			
1.1	ta, Kansas		0.0		Application Number	H	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COM		23		EVATION:		
A C	Depth(s) groundwa		1	ft.	2 ft.	3 ft.	
	ELL'S STATIC WA	ATER LEVEL 11	FT.	BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	09/22/1992	
NWNE	Pump test	data: Well wa	ater was	ft.	after hours pum	ping gpm	
	t. Yield	gpm: Well w	ater was	ft.	after hours pum	ping gpm	
E Bo	re Hole Diameter	_ in. t	to	ft.,	and in.	to ft.	
WI WI	ELL WATER TO	E USED AS: 5	Public wate		8 Air conditioning 11 I	njection well	
	1 Domestic		Oil field wa	ter supply	9 Dewatering 12 O	other (Specify below)	
SW SE	2 Irrigation	4 Industrial 7	Lawn and g	arden only 1	0 Monitoring well		
		riological sample sub		•		o/day/yr sample was	
e l	ubmitted	riologicai sample sub	matted to De	•			
5 TYPE OF CASING USED:	IDIRICCEU						
——————————————————————————————————————		5 Wrought iron		Concrete tile		lued Clamped	
		6 Asbestos-Cement	, 9	Other (Specify be	•	/elded	
2 PVC 4 ABS		7 Fiberglass			T	hreaded	
Blank casing Diameter 1 1/4 in.	. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing helght above hand surface 42	in. ,	welght		lbs. / ft.	Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION	N MATERIAL:			PVC	10 Asbestos-ceme	ent	
1 Steel 3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify))	
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (op	en hole)	
SCREEN OR PERFORATION OPENI	NG ARE:	5 Gauze	d wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot		6 Wire w			9 Drilled holes		
2 Louvered shutter 4 Key punch	ned	7 Torch			10 Other (specify)		
SCREEN-PERFORATION INTERVAL					,/	Δ.	
SCREEN-FERFORATION INTERVAL		ft. (to	ft., From	ft. to	ft.	
	from	ft. (to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVAL	LS: from	ft.	to	ft., From	ft. to	ft.	
	from	ft.		ft., From	1 ft. to	ft	
6 GROUT MATERIAL: 1 Neat cem	ent 2 <u>C</u>	ement grout	3 Ber	ntonite	4 Other		
Grout Intervals: From 3.5	t. to 9	ft., From	ft.	to	ft., From	ft. to ft.	
What is the nearest source of possible con	atamination:			10 Livesto		bandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel sto	orage 15 C	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon				16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction form well? West	F	•			How many feet? 25		
	HOLOGIC LOG		FROM	то	PLUGGING INTER	RVALS	
	-		0		dirt fill		
			3.5		cement grout		
			9		bentonite hole	ກໄນແ	
					chlorinated san		
			11	1 23 9	chiorinaced san	u and graver	
			 				
			ļ		1		
			 				
			<u> </u>				
			 				
			ļ				
			<u></u>				
7 CONTRACTOR'S OR LANDOWNER'S C	ERTIFICATION: This	s water well was (1)	constructe	ed, (2) reconstru	icted, or (3) <u>plugged</u> under m	y jurisdiction and	
was completed on (mo/day/year)							
Well Contractor's License No. 23.6 This Water Well Record was completed on (mo/day/yr) Q9/22/92 Under the business name of Harp Well & Pump Service. Inc. by (signature)							
Under the business name ofHAR	5 MeTT &)	Pump Servi	ceIr	ଧ୍ୟଲ by (signa	ature) M me s (H) o	dorink.	
118							