WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | | т- | | | |
|---|------------------|------------|---------------|---|--|
| County Location of well: | Fraction | | Section | | Township number Range number |
| Sedgwick | 1/4 SW 1/4 NE | 1/4 | 2 | 1 | T 26 S R 1E E/W |
| Distance and direction from nearest town or city: South Lot 1, 53rd and F | rimrose | 3. Owner | | ייי | eewood Homes Construction |
| | ita, Kansas | R.R. or st | | | 228 Primrose |
| 4. Locate with "X" in section below: | Sketch map: | City, sidi | e, 21p c | ode: Wa | ichita, Kansas 6. Bore hole dio. 11 in. Completion date |
| N | Sketch hidp: | | | | Well depth 60 ft. 4-1-78 |
| | | | | ı | 7Cable tool XRotaryDrivenDug |
| NW NE | | | | | Hollow rod Jetted Bored Reverse rotary |
| W | | | | | 8. Use: X Domestic Public supply Industry |
| | | | | | Irrigation Air conditioning Stock Lawn Oil field water Other |
| SW SE | | | | ļ | 9. Casing: MatSityrene Height: Above or below |
| 1 1 | | | | | Threoded Weldedg1 Surfacein. |
| S 1 Mile ———————————————————————————————————— | | | | | RMP X PVC Weight Ibs./ft. Dia. 5 in. to 60 ft. depth Wall Thickness: inches or |
| . Type and color of material | | T | From | То | Dio in. to ft. depth gage No 200 |
| | | | | | 10. Screen: Manufacturer's name Sunflower plastic |
| Topsoil | | | o | 3 | Type styrene Dia 5" |
| C1 | | | | 1.4 | Slot/galuke/06 Length25 |
| Clay | | | 3 | 14 | Set betweenft. andft. |
| Fine sand | | | 14 | 19 | Gravel pock? Yes. Size range of material 4-1/8" |
| Clay | | | 19 | 25 | 11. Static water level: mo./day/yr. 20 ft. below land surface Date 4-1-78 |
| Fine sand | | | 25 | 38 | 12. Pumping level below land surfaces: |
| Grey shale | | | 38 | 60 | ft. after hrs. pumping g.p.m ft. after hrs. pumping g.p.m. |
| | | | | | Estimated maximum yieldg.p.m. |
| | | | | | 13. Water sample submitted: mo./day/yr. |
| | | | | ŀ | Yes No Date 14. Well head completion: Canned |
| | | | | | 14. Well head completion: capped Pitless adapter 12 Inches above grade |
| | | | \rightarrow | | 15. Well grouted? yes 1-2 fine sand mix |
| | | | | | With: Neat cement Bentonite X Concrete Depth: From6 ft. to16 ft. |
| | | | | f | 16. Negrest source of possible contamination: |
| | | | | | ft Direction Type None |
| | | <u> </u> | | | Well disinfected upon completion? X Yes No 17. Pump: X Not installed |
| | | | | | Manufacturer's name |
| | | | | | Model number HP Volts |
| | | | \rightarrow | | Length of drop pipe ft. capocityg.p.m. Type: |
| | | | | | Submersible Turbine |
| (Use a second s | neet if needed) | | | | Jet Reciprocating Other |
| B. Elevation: 19. Remarks: | | | | | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report |
| . Flat ground | | | | is true to the best of my knowledge and belief. | |
| Sentic system not installed at this time | | | | Harp Well & Pump 236 | |
| Slope No apparent source for contamination | | | | business name | |
| 510PC | source for conta | minat | ion | | Business name Wichita, Kansas 67209 |
| 510PC | | minat | ion | | Business name Wichita, Kansas 67209°. Address Market Name Date Authorized representative |