

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>SW 1/4 SW 1/4 SW 1/4</u>	<u>26</u>	T <u>26</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3800 N. Hillside Wichita, Ks.</u>					
2 WATER WELL OWNER:					
RR#, St. Address, Box # : <u>KS INC</u>					
City, State, ZIP Code : <u>2617 Broadway Wichita, Ks</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>10</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>7.5</u> ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL <u>8.15</u> ft. below land surface measured on mo/day/yr <u>1/18/91</u>			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter: <u>8.5</u> in. to <u>10</u> ft., and . in. to . ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes. . No. ☒ If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . . . Clamped . . . <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . . . 7 Fiberglass Threaded . . .					
Blank casing diameter . <u>2</u> in. to . ft., Dia . in. to . ft., Dia . in. to . ft.					
Casing height above land surface . <u>12'</u> in., weight . lbs./ft. Wall thickness or gauge No. .					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) . . . 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) . . .					
SCREEN-PERFORATED INTERVALS: From . <u>10</u> ft. to . <u>7.5</u> ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From . <u>10</u> ft. to . <u>7.5</u> ft., From . ft. to . ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other . . . Grout Intervals: From . <u>3</u> ft. to . <u>10</u> ft., From . ft. to . ft., From . ft. to . ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>SE</u> How many feet? <u>174' S 45' E</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	VDK BR U/CLAY DEVELOPED ZONE			
1.5	7.5	RdH BR SM/CLAYEY SAND ALLUVIUM			PLUGGED W/ BENTONITE
7.5	10.0	BLUISH GR / WET / CLAYEY SAND			FROM 3-10'
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1/18/91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>3/25/91</u> under the business name of <u>Geotechnical Services Inc</u> by (signature) <u>Sandra Linace</u>					