


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County SEDGWICK	Fraction SE 1/4 SE 1/4 SW 1/4	Section number 28	Township number T 26	Range number S 1 R 1 E
2. Distance and direction from nearest town or city: Street address of well location if in city: 3903 N. HYDRAULIC WICHITA KS				3. Owner of well: REAL ESTATE MART City, state, zip code: 1550 30 BROADWAY WICHITA KANS		
4. Locate with "X" in section below: 				Sketch map: BORED 8" HOLE TO 10' IN STALLED 4" X 11' CASING - DRIVE PIPE + POINT TO COMPLETE CROUTED CASING		
5. Type and color of material				From	To	6. Bore hole dia. 8 in. Completion date 8-16-78 Well depth 26 ft. BASEMENT
CLAY BLACK				0	3	<input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input checked="" type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input checked="" type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
CLAY GRAY				3	7	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
CLAY - BROWN - SANDY				7	10	9. Casing: Material RMP Height: Above or below Threading SUL Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 1.55 lbs./ft. Dia. 4 in. to 11 ft. depth Wall Thickness: inches or Dia. 1 in. to 11 ft. depth gage No. 0.200
CLAY - BROWN SANDY				10		10. Screen: Manufacturer's name CLAYTON MARIZ Type BRASS Dia. 1.25 Slot/gauze 0.60 Length 4 FT. Set between 22 ft. and 26 ft. Gravel pack? NO Size range of material
DRIVE PIPE + POINT TO				26		11. Static water level: 12 ft. below land surface Date 8-16-78 mo./day/yr.
						12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping NA g.p.m. Estimated maximum yield 30 g.p.m.
						13. Water sample submitted: NO mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date
						14. Well head completion: 12 BASEMENT Pitless adapter 12 inches above grade
						15. Well grouted? YES With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: ft. 25 Direction NW Type CAST IRON Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
						17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number 26 HP 1 Volts 115 Length of drop pipe 26 ft. capacity NA g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
(Use a second sheet if needed)						
18. Elevation: 1300 Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN Pump & Well Business name License No. Address 3142 MENTOR WICHITA Signed O. W. Bearden Date 10-2-78 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5