

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE ¼ SW ¼ SE ¼		28		T 26 S		R 1 <u>EW</u>	
Distance and direction from nearest town or city street address of well if located within city?									
3900 N Bridgeport Wichita									
2 WATER WELL OWNER:		City of Wichita							
RR#, St. Address, Box # :		1900 East 9th Street				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Wichita KS 67214				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL . 44.0' ft. ELEVATION: N.A.							
		Depth(s) Groundwater Encountered 1. 18' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL . N.A. ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 8" in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>							
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>							
		TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded <u>2 PVC</u> 4 ABS 7 Fiberglass Threaded. <u>Flush Joint</u> . Blank casing diameter 2" in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface approx 30" in., weight 7.03 lbs./ft. Wall thickness or gauge No. 154							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From 9.0' ft. to 43.5' ft., From ft. to ft. From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS:		From 7.0' ft. to 43.5' ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From 7.0' ft. to 1.0' ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0.0'	3.5'	Top Soil.							
3.5'	18.0'	Silty Clay.							
18.0'	43.0'	Sand.							
43.0'	44.0'	Shale.							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-10-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 4-8-91 under the business name of Geotechnical Services, Inc. by (signature) <u>Alison Irwin</u>									