			Water Well R	ecord Form W	/WC-5_	KSA 82a-1212			
1 LOCATION OF W		FRACTION			T	Section Number	Township Number	Range Number	
Sedg		SW 1/4	SW 1/4	NE	1/4	29	т 26 s	R 1E E/W	
	_	y street address of well if loc	•						
500 W. 41st N. Wichita, Kansas									
WATER WELL OWNER: BEACH, Harry  RR#, ST. ADRESS, BOX#: 500 W. 41st N.  Board of Agriculture, Divivsion of Water Resource									
CITY, STATE, ZI		w. 41st N. Mita, Kansa					Application Numb		
3 LOCATE WELL'S		4 DEPTH OF COM		L 30		ft. ELEV	VATION:	п.	
AN "X" IN SECTIO		Depth(s) groundw			•	ft.	2 ft.	3 ft.	
		WELL'S STATIC W	ATER LEVEL	9	FT.	BELOW LAND SURI	FACE MEASURED ON mo/day/yr	10/11/1993	
	NE.	Pump tes	t data: We	ell water wa	ıs	ft. at	fter hours pun		
		Est. Yield	gpm: We	ell water wa	a.s	ft. a	ifter hours pun	nping gpm	
w Wile	X E	Bore Hole Diameter	12 in.	to 3(	0	ft.,	and in.	to ft.	
-		WELL WATER TO		5 Public				Injection well	
sw	sie	1 Domestic	3 Feedlot 4 Industrial			1. 7	•	Other (Specify below)	
		2 Irrigation			_	-	Monitoring well		
'	S	Was a chemical/bacto submitted	eriological sampl	e submitted	to Dep	-		no/day/yr sample was	
THE OF CASTAGE VICTOR									
1 Steel 3 RMP (SR) 5 Wrought iron 6 Asbestos-Cement						8 Concrete tile CASING JOINTS: Glued X Clamped 9 Other (Specify below) Welded			
2 PVC	4 ABS		7 Fiberglass			DR-26		Threaded	
Blank casing Dian	neter 5	in. to 24	ft., Dia		in.		ft., Dia in.	to ft.	
Casing height abo	ve land surface 1	2 in.,	,	2.35			Vall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel	3 Stainless Steel		5 Fiberglass		8	RMP (SR)	11 other (specif	y)	
2 Brass 4 Galvanized steel 6 Concrete tile					9.	9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed							8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 24 ft. to 30 ft., From ft. to ft.									
		from		ft. to		ft., From	ft. to	ft.	
				ft. to 30	)	ft., From		ft.	
6 GROUT MAT	ERIAL: 1 Neat of	ement 2.0	Sement grout	ft. to	3 Rone	ft., From	4 Other	<u>ft.</u>	
Grout Intervals: From A									
What is the nearest source of possible contamination:					ft. to ft., From 10 Livestock pens 14 Abs		ft. to ft. Abandon water well		
<u>-</u>			7 Pit priv	y	11 Fuel storage		rage 15	Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Se			8 Sewage l	agoon	12 Fertilizer storage		er storage 16	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? North How many feet? 75									
FROM TO 2		LITHOLOGIC LOG	· · · · · · · · · · · · · · · · · ·	FRO	<u>OM</u>	ТО	PLUGGING INTE	RVALS	
0 2 2 10	topsoil clay	· · · · · · · · · · · · · · · · · · ·							
10 30		o coarse s	and						
	mourum c	o coarse s	ana				1 200 (7)		
								AND	
		·							
							1.00		
						<del> </del>			
	L		<del></del>						
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Later Later Later Later Woll & Dumn Corvigo Inc.									
827    Some Frederick   Some of the purpose of the									