			WATE	R WELL RECORD	Form WWC-	5 KSA 82a-	1212				
LOCAT		TER WELL:	Fraction	_	i i	ction Number	Township N	Number	Range Numb	per	
County:			SE 1/2		NE 1/4	29	<u>  T 26 </u>	S	R 1E	E/W	
				address of well if locate	ed within city?						
300_	<u>West 41:</u>	st St. No.	Wi	chita,Ks.							
≥ WATE	R WELL OV	VNER: M.L. C									
RR#, St.	Address, Bo	× # : 300 We	est 41st S	t. No.			Board of	Agriculture,	Division of Water R	esources	
City, State	e, ZIP Code	Wichit	a.Ks.				Application	n Number:			
LOCAT	E WELL'S L ' IN SECTIO	N ROY∙ -	-4	COMPLETED WELL dwater Encountered							
Ī	NW	I NF -	Pum	WATER LEVEL p test data: Well wat gpm: Well wat	ter was	ft. af	ter	. hours pu	mping	gpm	
• l	<u>i</u>			eter $11$ in. to							
ž w	1			TO BE USED AS:	5 Public wat		8 Air conditionin		Injection well		
7	- I		1 Domestic	3 Feedlot	6 Oil field wa	ater supply	9 Dewatering	12	Other (Specify beld	ow)	
	3W	SE	2 Irrigation	4 Industrial	7 Lawn and	garden only 1	0 Monitoring we	<u> </u>			
l i	i	]	Was a chemical	bacteriological sample	submitted to E	Department? Ye	sNo	X; If yes	mo/day/yr sample	was sub	
		5   1	mitted			Wat	er Well Disinfect	ed? Yes	X No		
TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 Conc	rete tile	CASING JO	DINTS: Glue	d . X Clamped		
1 S	teel	3 RMP (SR	)	6 Asbestos-Cement	9 Other	(specify below	')	Weld	ed		
2 P	vc	4 ABS		7 Fiberglass	SD	R-26		Threa	aded		
Blank cas	ing diameter	·	n. to	.23 ft., Dia	in. to	o	ft., Dia		in. to	ft.	
Casing he	eight above I	and surface	12 .	.in., weight	2.29	Ibs./f	t. Wall thickness	or gauge N	0 214		
		R PERFORATION	•		7 P\			bestos-ceme			
1 S	teel	3 Stainless	steel	5 Fiberglass	8 RI	MP (SR)	11 Ot	her (specify)			
2 B	rass	4 Galvanize	d steel	6 Concrete tile	9 A	3S	12 No	ne used (op	en hole)		
SCREEN	OR PERFO	RATION OPENING	SS ARE:	5 Gau	zed wrapped		8 Saw cut		11 None (open h	ole)	
1 C	ontinuous sk	ot 3 Mill	l slot	6 Wire	wrapped		9 Drilled holes				
2 Lo	ouvered shut	ter 4 Key	y punched	7 Torc	h cut	_	10 Other (specif	fy)			
SCREEN-	PERFORAT	ED INTERVALS:	From	23 ft. to .		3ft., Fron	n	ft. t	0	ft.	
			From	ft. to .		ft., Fron	n <i></i>	ft. t	0	ft.	
	GRAVEL PA	CK INTERVALS:	From	20 ft. to .	43	ft., Fron	n	ft. t	0	ft.	
			From	ft. to		ft., Fron	1	ft. t	o	ft.	
GROU	T MATERIAI	L: 1 Neat ce	ement .	2 Cement grout	3 Bent	onite 4	Other				
Grout Inte	rvals: Fro	<sub>m</sub> <sub>f</sub>	t. to 20 .	ft., From	<i></i> ft.	to	ft., From .		ft. to	ft.	
What is th	ne nearest se	ource of possible c	ontamination:			10 Livest	ock pens	14 A	bandoned water we	ell	
1 Septic tank 4 Latera			l lines	7 Pit privy		11 Fuel storage			15 Oil well/Gas well		
2 Sewer lines 5 Cess			pool	8 Sewage lag	goon	oon 12 Fertilizer storage			16 Other (specify below)		
3 W	atertight sev	ver lines 6 Seepa	ge pit	9 Feedyard		13 Insect	icide storage				
Direction	from well?	North				How man	y feet?		85		
FROM	TO		LITHOLOGIC	LOG	FROM	то	P	LUGGING I	NTERVALS		
0	2	topsoi	.1								
2	6	sandy	tan clay								
6	19	fine t	o coarse	sand							
19	43	fine t	o coarse	sand fine to							
		mediu	m gravel								
									·· - · - · · · · · · · · · · · · · · ·	-	
	1										
J	DAOTOS:S	OD I ANDOMANICO	'S CERTIFICAT	ION: This water we'll	uge (1) const-	uoted (2) recei	netructed or (2)	plugged upo	ler my juriediation :	and was	
I CONT	HACTOR'S	OH LANDOWNER	7 10 00	ION: This water well v	vas (1) constr	and this race	die true to the L	hindaen nuc	owledge and holist	Kanasa	
completed	on (mo/day	year)	···\∸T?∸A∩	This Mater N	Mall Pagard	anu una recol	u is true to the D	est of filly Kg	- 30-de	Nambas	
				This Water V		as completed c	uro)		The sall		
	business na	me or Harp	Well and	Pump Service,	inc.	by (signate	7 / -	viet 1	umoed)		
INSTR	UCTIONS: Use lith and Environr	typewriter or ball point pe nent, Bureau of Water, ∃	en. <u>PLEASE PHESS</u> Topeka, Kansas 666	FIRMLY and PRINT clearly. I 20-7320. Telephone: 913-296-	riease iii in blanks 5545. Send one to	WATER WELL OV	THE CORRECT ANSWERS.  VNER and retain one	for your records	copies to Kansas Departr s.	nent	