

1 LOCATION OF WATER WELL: Fraction N 1/4 S 1/4 E 1/4 Section Number 30 Township Number T 26 S Range Number R 1 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?
See Below

2 WATER WELL OWNER: ROY FOSTER
 RR#, St. Address, Box #: 4201 N. Seneca
 City, State, ZIP Code: WICHITA KS 67204
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
 4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 17 ft.

Depth(s) Groundwater Encountered 1. 17 ft. 2. 17 ft. 3. 17 ft.
 WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 6-10-90
 Pump test data: Well water was 17 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 75 gpm; Well water was 17 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 50 ft., and 11 in. to 50 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 5 in. to 42 ft. Dia. 5 in. to 42 ft. Dia. 5 in. to 42 ft. Dia. 5 in. to 42 ft. Dia.
 Casing height above land surface 12 in., weight 2.52 lbs./ft. Wall thickness or gauge No 50R 160R

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 42 ft. to 50 ft. From 42 ft. to 50 ft. From 42 ft. to 50 ft. From 42 ft. to 50 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 50 ft. From 20 ft. to 50 ft. From 20 ft. to 50 ft. From 20 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 20 ft. From 3 ft. to 20 ft. From 3 ft. to 20 ft. From 3 ft. to 20 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? NE How many feet? 65

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	14	Clay			
14	32	fine sand			
32	34	clay			
34	50	med gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-19-90 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-19-90
 under the business name of Chambers Bully Inc by (signature) [Signature]