

1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SE 1/4 Section Number 30 Township Number T 26 S Range Number R 1 EW  
 County: Sedgwick  
 Distance and direction from nearest town or city street address of well if located within city?  
1522 Nottingham Lane, Wichita, KS

2 WATER WELL OWNER: Steven R. Howard  
 RR#, St. Address, Box #: 1522 Nottingham  
 City, State, ZIP Code: Wichita, KS 67204  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 32 1/2 ft. ELEVATION: 1518 1/2 ft. below land surface measured on mo/day/yr 7-14-91  
 Depth(s) Groundwater Encountered 1. 15 ft. 2. 18 1/2 ft. 3. 30 ft.  
 WELL'S STATIC WATER LEVEL 1518 1/2 ft. below land surface measured on mo/day/yr 7-14-91  
 Pump test data: Well water was 18 1/2 ft. after 1 hours pumping 30 gpm  
 Est. Yield 30 gpm: Well water was 18 1/2 ft. after 1 hours pumping 30 gpm  
 Bore Hole Diameter 8 in. to 15 ft., and 5 in. to 32 1/2 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 32 1/2 ft., Dia. 18 in. to 32 1/2 ft., Dia. 18 in. to 32 1/2 ft., Dia. 18 in. to 32 1/2 ft., Dia.  
 Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. Sch. 40  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 22 1/2 ft. to 32 1/2 ft., From 22 1/2 ft. to 32 1/2 ft., From 22 1/2 ft. to 32 1/2 ft., From 22 1/2 ft. to 32 1/2 ft.  
 GRAVEL PACK INTERVALS: From 22 1/2 ft. to 32 1/2 ft., From 22 1/2 ft. to 32 1/2 ft., From 22 1/2 ft. to 32 1/2 ft., From 22 1/2 ft. to 32 1/2 ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 9 ft., From 9 ft. to 15 ft., From 9 ft. to 15 ft., From 9 ft. to 15 ft.  
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Garage Foundation?  
 Direction from well? East How many feet? 8

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2 1/2	Topsoil			
2 1/2	3 1/2	Clay			
3 1/2	15	Clay sand mixture of various grades of sand			
15	32 1/2	Sand-various grades			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-14-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 7-14-91 This Water Well Record was completed on (mo/day/yr) 7-14-91 under the business name of Steven R. Howard by (signature) Steven R. Howard