

1 LOCATION OF WATER WELL: County: Sedgwick Fraction NE 1/4 SE 1/4 SE 1/4 NE 1/4 Section Number 30 Township Number 26 Range Number 1 EW

Distance and direction from nearest town or city street address of well if located within city? 150' N. of bldg. 130' W. of fence on Seneca St., 4141 N. Seneca

2 WATER WELL OWNER: Unified School Dist. 259 (Construction & Trans.Center) Well No. 1

RR#, St. Address, Box #: 428 S. Broadway Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Wichita, Ks. 67202 Application Number: 34521

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 1320

Depth(s) Groundwater Encountered: 10' 2" ft. 2. 12' 4" ft. 3. 35 ft.

WELL'S STATIC WATER LEVEL: 10' 2" ft. below land surface measured on mo/day/yr 3/10/87

Pump test data: Well water was 12' 4" ft. after 1 1/2 hours pumping 35 gpm

Est. Yield 28 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 12 in. to 40 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes 1/7/87 No: If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter: 2 x 6 in. to Steel 20 ft., Dia. 6 in. to PVC 30 ft., Dia. in. to ft.

Casing height above land surface: 48 in., weight 18.97 lbs./ft. Wall thickness or gauge No. 280

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 40 ft. to 30 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 40 ft. to 20 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? SW How many feet? 150

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/31/87 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 4/1/87

under the business name of Layne-Western Co., Inc., Wichita, Ks by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500 Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.