


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County SEDGWICK	Fraction SE 1/4 SW 1/4 SE 1/4	Section number 31	Township number T 26 S	Range number R 1 E
2. Distance and direction from nearest town or city: Street address of well location if in city		3. Owner of well: R.R. or street:		Completion date		
1521 W. 30th COURT NORTH - WICHITA KS		LEO ST. PETERS 1521 W. 30th COURT. NORTH WICHITA KANS 67204		5-16-79		
4. Locate with "X" in section below: 		Sketch map: DRILLED 9" HOLE TO 13' THEN 6" TO 16' - INSTALLED CASING + COMPLETED WITH SAND BUCKET AT 38'		6. Bore hole dia. 9 in. Completion date 5-16-79 Well depth 38 ft. FROM GRADE		
5. Type and color of material		From	To	7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input checked="" type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
TOP SOIL BLACK		0	3	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
SANDY CLAY BROWN		3	7	9. Casing: Material RMP Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 1.55 lbs./ft. Dia. 5 in. to 39 ft. depth Wall Thickness: inches or Dia. 5 in. to 39 ft. depth gage No. 0.200		
SAND FINE TAN-		7	10	10. Screen: Manufacturer's name SANFLOWER Type RMP Dia. 5 INCH Slot/gauze .031 Length 7 FT. Set between 31 ft. and 38 ft. ft. and ft. Gravel pack? NO Size range of material		
SAND MED. TAN		10	16	11. Static water level: 16 ft. below land surface Date 5-16-79 mo./day/yr.		
SAND COARSE BROWN		16	20	12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 65 g.p.m.		
GRAVEL - COARSE BROWN		20	24	13. Water sample submitted: NO Date 5-16-79 Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date		
CLAY BLACK		24	25	14. Well head completion: 12 inches above grade <input checked="" type="checkbox"/> Pitless adapter 12 inches above grade		
SAND COARSE GRAY		25	29	15. Well grouted? YES With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 31 ft. to 13 ft.		
SAND COARSE TAN		29	38	16. Nearest source of possible contamination: PLASTIC ft. 40 Direction 30 Type SEWER Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: CUSTOMERS PUMP Manufacturer's name STARITE Model number UNKNOWN HP 1.5 Volts 230 Length of drop pipe 25 ft. capacity 15 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation: 1300' Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input checked="" type="checkbox"/> Valley		19. Remarks: OWNER WILL CONSTRUCT 4" X 4' X 4' SLAB -		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMPWELL Business name 3402 MENTON - WICHITA License No. 164 Address 3402 MENTON - WICHITA Signed Oliver Bearden Date 6-18-79 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5