

1 LOCATION OF WATER WELL:		FRACTION		Section Number	Township Number	Range Number
Sedgwick		SE 1/4	SE 1/4	NW 1/4	31	T 26 S R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?						
3443 N. Amidon Wichita, Kansas						
2 WATER WELL OWNER:		WALL, Dr. David				
RR#, ST. ADDRESS, BOX #:		3443 N. Amidon				
CITY, STATE, ZIP CODE:		Wichita, Kansas				
Board of Agriculture, Division of Water Resource						
Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 45 ft. ELEVATION:				
<div style="text-align: center;"><p>1 Mile</p></div>		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.				
		WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 09/25/1992				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 12 in. to 45 ft., and in. to ft.				
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well				
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No						
5 TYPE OF CASING USED:						
1 Steel 3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
2 PVC 4 ABS		6 Asbestos-Cement		9 Other (Specify below)		Welded
		7 Fiberglass		SDR-26		Threaded
Blank casing Diameter 5 in. to 25 ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless Steel		5 Fiberglass		8 RMP (SR)		11 other (specify)
2 Brass 4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE:						
1 Continuous slot 3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)
2 Louvered shutter 4 Key punched		6 Wire wrapped		9 Drilled holes		
SCREEN-PERFORATION INTERVALS: from 25 ft. to 45 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: from 24 ft. to 45 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandon water well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)
None Apparent						
Direction from well? How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	3	topsoil				
3	12	clay				
12	21	fine sand				
21	45	medium sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/25/1992 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10/30/92 Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick						