


1 LOCATION OF WATER WELL: County: <u>Sedgewick</u>	Fraction <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>33</u>	Township Number T <u>26</u> S	Range Number R <u>1</u> <u>EW</u>
---	---	-----------------------------	----------------------------------	--------------------------------------

Distance and direction from nearest town or city street address of well if located within city?

In Wichita: -

2 WATER WELL OWNER: <u>Keebler Warehouse</u> RR#, St. Address, Box #: <u>3629 N. Hydraulic</u> City, State, ZIP Code: <u>Wichita, KS</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>25'6"</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>17'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: <u>16.00</u> ft. below land surface measured on mo/day/yr <u>11-24-93</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>7 1/2"</u> in. to <u>25'6"</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>
---	--

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> 3 RMP (SR) 4 ABS Blank casing diameter <u>2.42</u> in. to <u>15'</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface <u>Flush Mount</u> , weight lbs./ft. Wall thickness or gauge No. <u>SDR-13</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement <u>Sch 40</u> 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From <u>25'</u> ft. to <u>15'</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>25'</u> ft. to <u>13'</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.	CASING JOINTS: Glued Clamped Welded Threaded <u>X</u>
--	---

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>13'</u> <u>3'</u> ft., From <u>3'</u> ft. to <u>0'</u> ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage <u>Manufacturing plant</u> Direction from well? <u>East</u> How many feet? <u>50'</u> <u>Colman</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.75	Ls. & gravel			
1.75	2.0	dk Brown clay			
2.0	8.5	Med Brown clay, iron oxides			
8.5	11.0	" Reddish Brown clayey silt to silty clay			
11.0	18.0	Med Brown clay w/ iron oxides, fine-med grained ls. & qtz grains			
18.0	25'6"	Fine-coarse grained sand, wet sub rounded, well graded			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-24-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>11-27-93</u> under the business name of <u>QB Environmental Drilling</u> by (signature) <u>James Keebler</u>
--