


1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: NE 1/4 SE 1/4 NW 1/4 Section Number: 34 Township Number: T 36 S Range Number: R 10 E

Distance and direction from nearest town or city street address of well if located within city? 3600 N. HYDRAULIC WICHITA, KS

2 WATER WELL OWNER: COLEMAN CO. Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 3600 N. HYDRAULIC Application Number: MW 80
City, State, ZIP Code: WICHITA, KS

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: 40 ft.
Depth(s) Groundwater Encountered: 18 ft. 2. 18 ft. 3. 18 ft.
WELL'S STATIC WATER LEVEL: 18 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 18 ft. after 40 hours pumping 18 gpm
Est. Yield 18 gpm: Well water was 18 ft. after 40 hours pumping 18 gpm
Bore Hole Diameter: 8 in. to 40 ft., and 40 in. to 40 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted 10
Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded
Blank casing diameter 2 in. to 29 ft., Dia 29 in. to 29 ft., Dia 29 in. to 29 ft.
Casing height above land surface 0 in., weight 29 lbs./ft. Wall thickness or gauge No. 29
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 12 None used (open hole)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 39 10 Other (specify) 39
SCREEN-PERFORATED INTERVALS: From 29 ft. to 39 ft., From 29 ft. to 39 ft., From 29 ft. to 39 ft.
GRAVEL PACK INTERVALS: From 24 ft. to 40 ft., From 24 ft. to 40 ft., From 24 ft. to 40 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 29 ft., From 29 ft. to 29 ft., From 29 ft. to 29 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) PLANT
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? N How many feet? 50'

LITHOLOGIC LOG
FROM TO
0 25 SILTY SANDY CLAY
25 TO CLAY w/ FINE SAND

PLUGGING INTERVALS
FROM TO

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/5/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 100 This Water Well Record was completed on (mo/day/yr) 2/25/93 under the business name of LAYNE, INC. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.