

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																																	
County: Sedgwick		NE 1/4 SE 1/4 SE 1/4		32		T 26 S		R 1																																																	
Distance and direction from nearest town or city street address of well if located within city?								EAST																																																	
3145 North Broadway, Wichita, Kansas								HWST Job No.: 74-40/4015.01																																																	
2 WATER WELL OWNER: FDIC																																																									
RR#, St. Address, Box # : 9525 W. Bryn Mawr																																																									
City, State, ZIP Code : Rosemont, IL 60018																																																									
Board of Agriculture, Division of Water Resources																																																									
Application Number:																																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: 18.0 ft. ELEVATION: unknown																																																					
<div style="text-align: center;"><p>1 Mile</p></div>				Depth(s) Groundwater Encountered 1. 11.0 ft. 2. ft. 3. ft.																																																					
				WELL'S STATIC WATER LEVEL 10.82 ft. below land surface measured on mo/day/yr 6/1/90																																																					
				Pump test data: Well water was ft. after hours pumping gpm																																																					
				Est. Yield gpm: Well water was ft. after hours pumping gpm																																																					
				Bore Hole Diameter 6.5 in. to 18 ft. and in. to ft.																																																					
WELL WATER TO BE USED AS:																																																									
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well																																																									
2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)																																																									
10 Monitoring well MW-1																																																									
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted																																																									
Water Well Disinfected? Yes No X																																																									
5 TYPE OF BLANK CASING USED:																																																									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped																																																									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded																																																									
7 Fiberglass Threaded X																																																									
Blank casing diameter 2 in. to 18.0 ft. Dia in. to ft. Dia in. to ft.																																																									
Casing height above land surface flush in. weight lbs./ft. Wall thickness or gauge No. Sch. 40																																																									
TYPE OF SCREEN OR PERFORATION MATERIAL:																																																									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement																																																									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)																																																									
12 None used (open hole)																																																									
SCREEN OR PERFORATION OPENINGS ARE:																																																									
1 Continuous slot X Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)																																																									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes																																																									
7 Torch cut 10 Other (specify)																																																									
SCREEN-PERFORATED INTERVALS: From 8.0 ft. to 18.0 ft. From ft. to ft. From ft. to ft.																																																									
GRAVEL PACK INTERVALS: From 6.0 ft. to 18.0 ft. From ft. to ft. From ft. to ft.																																																									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite X Other Volclay Grout																																																									
Grout Intervals: From 1.0 ft. to 4.0 ft. From ft. to ft. From ft. to ft.																																																									
What is the nearest source of possible contamination:																																																									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well																																																									
2 Sewer lines 5 Cess pool 8 Sewage lagoon X1 Fuel storage 15 Oil well/Gas well																																																									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)																																																									
13 Insecticide storage																																																									
Direction from well? North How many feet? 200.0 ft.																																																									
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0.0</td><td>1.0</td><td>Fill:</td><td></td><td></td><td></td></tr><tr><td>1.0</td><td>1.5</td><td>Concrete:</td><td></td><td></td><td></td></tr><tr><td>1.5</td><td>6.0</td><td>Sandy Clay: dark brown mottled with light brown; 5-10% very fine sand; high plasticity.</td><td></td><td></td><td></td></tr><tr><td>6.0</td><td>7.0</td><td>Sandy Clay: light brown mottled with orange-brown and gray; 10-20% very fine sand; medium to high plasticity.</td><td></td><td></td><td></td></tr><tr><td>7.0</td><td>10.0</td><td>Sandy Silt: light brown; 20-30% very fine sand; 5-10% mica; moist @ 9.0'.</td><td></td><td></td><td></td></tr><tr><td>10.0</td><td>14.0</td><td>Sand: light brown; very fine sand; well sorted; wet @ 11.0'.</td><td></td><td></td><td></td></tr><tr><td>14.0</td><td>18.0</td><td>Sand: light brown; fine sand; poorly sorted; 10-20% small pebbles.</td><td></td><td></td><td></td></tr></tbody></table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0.0	1.0	Fill:				1.0	1.5	Concrete:				1.5	6.0	Sandy Clay: dark brown mottled with light brown; 5-10% very fine sand; high plasticity.				6.0	7.0	Sandy Clay: light brown mottled with orange-brown and gray; 10-20% very fine sand; medium to high plasticity.				7.0	10.0	Sandy Silt: light brown; 20-30% very fine sand; 5-10% mica; moist @ 9.0'.				10.0	14.0	Sand: light brown; very fine sand; well sorted; wet @ 11.0'.				14.0	18.0	Sand: light brown; fine sand; poorly sorted; 10-20% small pebbles.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																				
0.0	1.0	Fill:																																																							
1.0	1.5	Concrete:																																																							
1.5	6.0	Sandy Clay: dark brown mottled with light brown; 5-10% very fine sand; high plasticity.																																																							
6.0	7.0	Sandy Clay: light brown mottled with orange-brown and gray; 10-20% very fine sand; medium to high plasticity.																																																							
7.0	10.0	Sandy Silt: light brown; 20-30% very fine sand; 5-10% mica; moist @ 9.0'.																																																							
10.0	14.0	Sand: light brown; very fine sand; well sorted; wet @ 11.0'.																																																							
14.0	18.0	Sand: light brown; fine sand; poorly sorted; 10-20% small pebbles.																																																							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/29/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 6/1/90 under the business name of HWS Technologies Inc. by (signature)																																																									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																									