					Water Well Red	cord Form WW						
			FRACTION				Section Numi			Range Numbe	#	
Sedgwick NE 1/4					SE 1/4	19	т 2	6 s	R 1E	E/W		
Distance and direction frem nearest town or city street address of well if located within city?												
4945 Sullivan Wichita, Kansas												
ш	TER WELL O		R, Byr							_		
RR#,	ST. ADRESS,		Sulliv				Board of Agriculture, Divivision of Water Resource					
CITY	, STATE, ZIP	code: Wichi	ta, Ka		67204 Applica					r:		
3 LOCATE WELL'S LOCATION WITH DEPTH OF COMPLETED WELL 35 ft. ELEVATION:												
AN "A	'IN SECTION	N BOX:	Depth(s) gro	undwater !	Encountered		ft.	2	ft.	3	ft.	
l		W	ÆLL'S STAT	IC WATE	R LEVEL	25	FT. BELOW LAN	D SURFACE MEASURE	D ON mo/day/yr	08/15/19	994	
NW					ı: We	ell water was	ft	. after	hours pum	ping	gpm	
			ıt. Yieid			ell water was	ft	t. after	hours pum	ping	gpm	
ag w	-	1 1 (12)	re Hole Diam		12 in.	to 35	ft.	and	in.	to	ft.	
=	1	X w	ELL WATER	t TO BE U	SED AS:	5 Public wa	ater supply	8 Air condition	_	njection well		
١,	sw	SIE	1 Domestic		Feedlot	6 Oil field	water supply	9 Dewatering		Other (Specify belo	W)	
2 Irrigation					4 Industrial 7 Lawn and garden only 10 Monitoring well							
			'as a chemical	/bacteriolo	gical sample	submitted to	Department? Y	res N	o 🗶 ; If yes, m	o/day/yr sample w	as	
	*·		ubmitted					Water Well Disinfo	cted? Yes	X No		
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped												
1 Stee	l	3 RMP (SR)			6 Asbestos-Cement 9 Other (Spec			fy below) Welded				
2 PVC	2	4 ABS		7]	Fiberglass		SDR-26	-	Т	hreaded		
Blank ca	_ sing Diam	eter 5 in	L to 25	f	ft. , Dia		in. to	ft., Dia	in.	to ft.		
		e land surface 12		in.,	•	2.35	lbs. / ft.	Wall thickness		.214		
		N OR PERFORATION	ON MATERL		"·B	2.00	7 PVC		0 Asbestos-ceme			
1 Stee	el	3 Stainless Steel		5 F	'iberglass		8 RMP (SR)		11 other (specify)		
2 Bras	s	4 Galvanized steel		6 C	oncrete tile		9 ABS		12 None used (or	en hole)		
SCREE	N OR PER	REFORATION OPENI	ING ARE:		5 G	auzed wrappe	мÌ	8 Saw cut		11 None (open	hole)	
5	nous slot	3 Mill slot	,1110			ire wrapped	•	9 Drilled h	- oles			
1	red shutter		·hed			orch cut		10 Other (snecify)			
		RATION INTERVAL		- 0E			A 1	`	,		ft.	
SCHLL.	Val Pive Ca	KATION INTERVAL		25		ft. to 35	•	From -	ft. to			
from				-	ft. to ft. to 35			From	ft. to		ft.	
GRAVEL PACK INTERVALS: from 24					ft. to 35		•	From From	ft. to ft. to		ft. A	
∠ GRO	UT MATI	ERIAL: 1 Neat cen			nt grout		Bentonite	4 Other	10 Y.			
			ft. to 24		ft. From					ft. to		
Grout Intervals: From 4 ft. to 24 What is the nearest source of possible contamination:					π. From π.		ft. to 10 Liv	ft. Fro vestock pens	n. 14 Abandon water well		ft. 1	
1 Septi		4 Lateral li			7 Pit privy	v		11 Fuei storage		15 Oil well/Gas well		
2 Sewer lines 5 Cess pool					8 Sewage la	-		ertilizer storage		on wen/Gas wen Other (specify belo	way)	
1	r mies rtight sewe	-			9 Feedyard	12 Images			cticide storage			
	n from wel	FB	: pit		7 Fecupato			**				
FROM			THOLOGIC	LOC		FRO	м то		feet? 80 UGGING INTE	DVATS		
0	3	topsoil	IIIODOGIC.		W-1-7-7	1	" ``	***	UGGIII G II I I I	XVPLIN		
3	12	clay				-+						
12	21	fine sand				 						
21	35	medium sa										
4	35	Meatam se	na									
								-				
	 			L		+-						
						+-						
	 							+	· · · · · · · · · · · · · · · · · · ·			
 						+-						
	 		 									
	 										#T-F	
												
						-						
ļ												
<u></u>												
7 CON	TRACTO	R'S or landowner's	CERTIFICATION	N: This wa	ater well wa	s (1) <u>constr</u> i	<u>ıcted, (2) reco</u> i	nstructed, or (3) p	lugged under n	ny jurisdiction an	nd	
was co	mpleted o	on (mo/day/year)	08/1	15/.199	₹.4	and this	record is true	to the best of my	knowledge and	belief. Kansas V	Nater	
Well Contractor's License No. 236												
Under	the busin	ess name of出品に	b Merr	aPw	mpser	vice	IRG by (signature)	n 9	rederick		
									Vana -t	hadahiah		

Œ