1 LOCA	TION OF WA	TER WELL:	FRACTION	v	MEL WEILKE	talu Fo	m wwc-s	Section Number	Township Number	Range Number
Щ.	Sedgw	ick NE	NW	1/4 NW	1/4	SE	1/4	29	T 26 s	R 1E EW
Distance		frem nearest town or city stree							1 1 20 3	
4153 N. Dale Wichita, Kansas										
					<u>s</u>					
	TER WELL (Roard of Agriculture	, Divivsion of Water Resource
4253 R. Dale										
	, STATE, ZIP	1 1							Application Num	iber:
	TE WELL'S L " IN SECTIO	N DOV.		F COMPLET			35		EVATION:	
Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.										
ΙĪ		WE	LL'S STAT	TIC WATER	LEVEL	15	FT	. BELOW LAND SU	RFACE MEASURED ON mo/day/yr	09/08/1994
	NW	NE	Pur	np test data:	We	ll water	r was	ft.	after hours pu	ımping gpm
	1	Est.	Yield	gpm:	We	ell water	r was	ft.	after hours pu	ımping gpm
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	/	E Bore	Hole Dian	neter 12	in.	to	35	ft.	and in	L to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection we								Injection well		
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									? Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring weli									
		Was	a chemical	l/bacteriologic	al sample	submit	ted to D	epartment? Yes	No X; If yes,	, mo/day/yr sample was
S submitted Water Well Disinfected? Yes X No										
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								•		
2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded										
	 asing Diam		to 24		Ū		in.		ft., Dia in.	to ft.
1	•	_	~ 44	,		2 3			Wall thickness or gauge No.	.214
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)										ify)
2 Bra	188	4 Galvanized steel		6 Con	crete tile		9	O ABS	12 None used ((open hole)
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
Torcheu										
SCREE	n-i erro	RATION INTERVALS		¹ 24			30	ft., From		
	CD 417		fron			ft. to	25	ft., From		
GRAVEL PACK INTERVALS: from 24					ft. to 35			ft., Fron		
from ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonlte 4 Other										
Chout Intervals. From A										
What is the nearest source of possible contamination: 10 Livestoc						ft. From	ft. to ft. Abandon water well			
		4 Lateral line					11 Fuel st		1	
				8 Sewage lagoon					5 Oil well/Gas well 6 Other (specify below)	
13 Incarticida etorga							5 Other (specify below)			
waterught sewer thies 6 Seepage pit 9 reedyard										
Direction from well? West					FROM			TO 1	How many feet? 50	PDVATS
0	2	topsoil	OLUGIC	LVG		-+	FROM	ТО	PLUGGING INT	ERVALO
2	15	sandy clay		. =	-	-+				
<u> 1</u> 5	35	medium san				-		+ +		
13	133	medium san	<u>u</u>							
						\dashv				
	1					-+		+		
—	 					-+		+ +		
	 					— -		+ +		
—	 							1		
								-		
	1 -	L				-+		+ +		
!								 		
	_	·						1	- 11 - 114 to - 44 to - 12 to	
	ļ							+		
<u></u>	J									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and										
was completed on (mo/day/year)										
Well (Contractor	's License No2.3	<u> </u>	This W	ater Wel	l Recor	rd was c	ompleted on (m	o/day/yr)QՁ./.	12/94
Under the business name of Harp Well & Pump Service, Inc by (signature)										
									Jane	Frederick
									ll.	