1 LOCATION OF WATER WELL:		FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number		
Sedgwick		SE 1/4	NE 1/4 P	IE 1/4	19	т 26 s	R 1E EW		
Distance and direction frem nearest town or city street address of well if located within city?									
5200 N. Sullivan Wichita, Kansas									
	TER WELL C		ARD, Jef		' 				
RR#, ST. ADRESS, BOX#: 5200 N. Sullivan Board of Agriculture, Divivision of Water Resource									
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:								per:	
LOCATE WELL'S LOCATION WITH DEPTH OF COMPLETED WELL 45 ft. ELEVATION:									
* *	IN DECTION	N I		ater Encountered	. 1	ft.	2 ft.	3 ft.	
				ATER LEVEL 12			RFACE MEASURED ON mo/day/yr	10/04/1994	
'	WW	NE X	Pump test Yield		vater was water was	ft. ft.	after hours pu	1	
13 W		1 1 1	Hole Diameter	gpm: Well 12 in.	to 45	rt. ft.	after hours pu		
¥ w	/		LL WATER TO I		5 Public wate			Injection weli	
١.			1 Domestic		6 Oil field wa		-	Other (Specify below)	
	SW-		2 Irrigation	4 Industrial	7 Lawn and g	garden only	10 Monitoring well		
₩as a chemical/bacteriological sample submitted to Department? Yes No 🗶 ; If yes, mo/day/yr sample was									
S submitted Water Well Disinfected? Yes X No									
\vdash		SING USED:		5 Wrought iron 8 Concrete tile			CASING JOINTS: Glued X Clamped		
1 Stee		3 RMP (SR)		6 Asbestos-Ceme	-	Other (Specify b	elow)	Welded	
2 PVC 4 ABS 7 Flberglass SDR-26 Threaded									
Blank casing Diameter 5 in. to 35 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No 214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREE	N-PERFO	RATION INTERVALS	: from 35	ft.	to 45	ft., From	n ft. to	ft.	
			from	ft.	to	ft., Fron	n ft. to	ft.	
	GRAVI	EL PACK INTERVALS							
from ft. to ft., From ft. to 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other)ft.	
Count Intervals. From A									
What is the nearest source of possible contam				IL FIUII	11.	10 Llvesto	ft. From ock pens 14	Abandon water well	
1 Septic tank 4 Lateral lin			es	7 Pit privy		11 Fuel st	orage 15	Oil well/Gas well	
2 Sewer lines 5 Cess poo				8 Sewage lagoon				Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
	n from wel		101 0010		 		How many feet? 80		
FROM O	<u>то</u>		HOLOGIC LOG		FROM	TO	PLUGGING INT	ERVALS	
3	6	topsoil clay							
6	21	fine sand							
21	45	medium san	đ	* ***					
					1		· · · · · · · · · · · · · · · · · · ·		
			- 1						
ļ									
 	1				-				
<u> </u>	-		· · · · · · · · · · · · · · · · · · ·			1 1			
 						_			
					-	++		and the Tri	
					1				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Well Contractor's License No									
Under the business name of Harp Well & Pump Service. Inc. by (signature) Jane Frederick									
	the busin	ess name ofHARD	Well &	Pump Serv	ice,I	AC by (sign	nature)	Fradarial	