1 LOC	ATION OF W	ATER WELL:	FRACTION	VE NW S	IN AF	Section Number	Township Number	Range Number
尸	Sedg	vick	15h 1/4			7	T 26 s	R 1E EW
Distance and direction frem nearest town or city street address of well if located within city?								
69th North and Interurban Wichita, Kansas								
	TER WELL			AT.	Chica, Ko	ansas		
	ST. ADRESS		, kon Interurb	.			Board of Agriculture, D	ivivsion of Water Resource
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:								
		LOCATION WITH 4		OMPLETED W	ELL 35	ft. EL	EVATION:	
	" IN SECTIO			dwater Encounte	-	n. El.	2 ft.	3 ft.
l t		TX T	ELL'S STATIC		_		RFACE MEASURED ON mo/day/yr	10/03/1994
1	i		-	<u>-</u>	Well water was	ft.	after hours pum	
•	NW	NE	t. Yield		Well water was	n. ft.	after hours pum	· . · · · · · · · · · · · · · · · · · ·
1 Mile			re Hole Diamete	4.0	in. to 35	ft.	and in.	ping gpm to ft.
🚡 v	[']	1 1 1 1 1 1	ELL WATER TO					njection well
			1 Domestic	3 Feedlot	6 Oil field w		-	Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was								
S submitted Water Well Disinfected? Yes X No								
TUDE OF CACING LICED.								
5 Wrought Iron 8 Co						O Other (Specify below) O Charles CASING JOINTS: Glued & Clamped Welded		
2 PV	C	4 ABS		7 Fiberglas		` - •	<i>'</i>	Threaded
5DR-20								
	_	•		,	Dia ir mb+225	ı. to lbs./ft.	ft., Dia in.	to ft.
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Bra	88	4 Galvanized steel		6 Concrete t	ile	9 ABS	12 None used (o)	·
20 1								
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
/ Toren cut								
10000								
GRAVEL PACK INTERVALS: from 24				0.4	ft. to ft. to 35			ft.
from					ft. to 35 ft., From ft. to ft., From			ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.								
What a decrease of the second						bandon water well		
1 Septic tank 4 Lateral lines			7 Pit p	7 Pit privy 11 Fu		el storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool				8 Sewag	8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent								
Direction from well? How many feet?								
FROM			HOLOGIC LO	G	FROM	TO	PLUGGING INTE	RVALS
0	3	topsoil						
3	14	clay		***			SEPTIC SYSTEM N	OT INSTALLED
14	23	fine sand					AT THIS TIME	
23	35	medium sar	nd					
<u> </u>			******					
<u> </u>	ļ							
	 		wa.				and the language and the	
ļ							- F-W-11-11-11-11-11-11-11-11-11-11-11-11-1	
	_							
			-			1		
ļ	ļ		·			+		
	 			-84-4				
<u> </u>	<u> </u>							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well C	ontractor	's License No2	36	This Water V	Vell Record was	completed on (m	o/day/yr)10./ 0	4/94
Under the business name of Harp Well & Pump Service, Inc by (signature)								
Jane Frederick								
1								