1 LOCATION OF WATER WELL: FRACTION Section Number Township Number	Range Number
	<u> </u>
Sedgwick SW 1/4 NW 1/4 SE 1/4 7 T 26 S  Distance and direction from nearest town or city street address of well if located within city?	R 1E E/W
į daras dara	
6404 Legion Wichita, Kansas    2   WATER WELLOWNER: DICKENS, Rita	
	griculture, Divivsion of Water Resource
1	ation Number:
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:	
MAN "Y" IN SECTION BOY:	ft. 3 ft.
WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON 1	no/day/yr 11/16/1994
Pump test data: Well water was ft. after h	ours pumping gpm
Est. Yield gpm: Well water was ft. after h	ours pumping gpm
Bore Hole Diameter 12 in. to 40 ft. and	in. to ft.
WELL WATER TO BE USED AS: 5 ruble water supply 8 Air conditioning	11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	12 Other (Specify below)
	. If we was /dev/www.commiss.
Was a chemical/bacteriological sample submitted to Department? Yes No X submitted Water Well Disinfected?	; If yes, mo/day/yr sample was Yes Y No
TANDE OF STREET	
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOIN 6 Asbestos-Cement 9 Other (Specify below)	Welded & Clamped Welded
2 PVC 4 ABS 7 Flberglass SDR-26	Threaded
Blank casing Diameter 5 in. to 25 ft., Dia in. to ft., Dia	in. to ft.
Casing helght above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gau	<del></del> ••
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Ash	estos-cement
1 Steel 3 Stainless Steel 5 Flberglass 8 RMP (SR) 11 other	er (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 Non	e used (open hole)
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify	)
SCREEN-PERFORATION INTERVALS: from 25 ft. to 35 ft., From	ft. to
from ft. to ft., From	ft. to ft.
GRAVEL PACK INTERVALS: from 24 ft. to 40 ft., From	ft. to ft.
from ft. to ft., From	ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonlte 4 Other	i
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From  What is the nearest source of possible contamination: 10 Livestock pens	ft. to ft.
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage	14 Abandon water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage	15 Oil well/Gas well 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? East How many feet?	100
	NG INTERVALS
0 3 topsoil	
3 12 clay	
12 25 fine sand	
25 35 medium sand	# 4 (# H. )
35 40 grey clay & dirty fine sand	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged	lunder my jurisdiction and
was completed on (mo/day/year)	
Well Contractor's License No236 This Water Well Record was completed on (mo/day/yr)	12/08/94
Under the business name of Harp Well & Pump Service, Inc., by (signature)	
Ja	ne Frederick
$\mathcal{A}^{a}$	ne creaerick