

1 LOCATION OF WATER WELL: County: <u>Sedgewick</u>	Fraction <u>SE 1/4</u> <u>SE 1/4</u> <u>NE 1/4</u>	Section Number <u>33</u>	Township Number <u>T 26 S</u>	Range Number <u>R 1 E</u>
---	---	-----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

250 North St. Francis, Wichita

2 WATER WELL OWNER: <u>Coleman Corporation</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>250 North St. Francis</u>	Application Number:
City, State, ZIP Code: <u>Wichita, Ks 67202</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S	4 DEPTH OF COMPLETED WELL: <u>38</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>1</u> ft. 2. <u>1</u> ft. 3. <u>1</u> ft. WELL'S STATIC WATER LEVEL <u>1</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>1</u> ft. after <u>1</u> hours pumping <u>1</u> gpm Est. Yield <u>NA</u> gpm Well water was <u>1</u> ft. after <u>1</u> hours pumping <u>1</u> gpm Bore Hole Diameter <u>12</u> in. to <u>38</u> in. to <u>1</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>1</u> No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>1</u> No <u>X</u>
--	---

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter <u>2</u> in. to <u>28</u> in. Dia. <u>1</u> in. to <u>1</u> in. Dia. <u>1</u> in. to <u>1</u> in. Casing height above land surface <u>0</u> in. weight <u>1</u> lbs. ft. Wall thickness or gauge No. <u>Schedule 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>28</u> ft. to <u>38</u> ft. From <u>1</u> ft. to <u>1</u> ft. From <u>1</u> ft. to <u>1</u> ft. From <u>1</u> ft. to <u>1</u> ft. GRAVEL PACK INTERVALS: From <u>22</u> ft. to <u>52</u> ft. From <u>1</u> ft. to <u>1</u> ft. From <u>1</u> ft. to <u>1</u> ft. From <u>1</u> ft. to <u>1</u> ft.
--

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>0</u> ft. to <u>2</u> ft. From <u>2</u> ft. to <u>24</u> ft. From <u>1</u> ft. to <u>1</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage <u>Unknown</u> Direction from well? <u>NA</u> How many feet? <u>NA</u>
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil, brown			MWNE-4D
2	7	Silty Clay, brown			Flush-mount Cover
7	10	Sand, tan			
10	13	Sandy clay, light brown			
13	15	Silty Clay, dark brown			
15	33	Sand, brown			
33	38	Sandy Clay, brown			
38	41	Clay, gray			
41	44	Clay with Sand, gray			
44	47	Clay, gray			
47	52	Clay with Sand, gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4/9/95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>527</u> This Water Well Record was completed on (mo/day/yr) <u>4/28/95</u> under the business name of <u>GeoCore Services, Inc.</u> by (signature) <u>Paul Kelli</u>
