LOCATION	U OE WATER	2 WELL.	Fraction	TTAILI			Secti	on Nur	nber		hip Numb		Da	nge Numi	her
			NW		NW ½	SE		3	11061		nip Numb <b>26</b>	rei S	R	- 4-	E
			own or city stre										· · · · · ·		
			e: 96.29595												
WATER W	ELL OWNE	R: TOTA	AL Petroch	nemic	als USA,	Inc.									
- R#, St. Addr	ress, Box #	: 1201	Louisiana	St., 9	Ste. 1800					Board of	Agricultu	ıre, Divi	ision of V	Nater Res	ources
					Application Number:										
LOCATE V	WELL'S LOC	ATON WIT	'HI . I												
AN "X" IN	SECTION B	OX:			MPLETED V										
,		i 1	Depth(s) G	roundw	ater Encount	tered 1			ft.	2		ft.	3		ft.
	NW	- NE	WELL'S ST	TATIC V	VATER LEVE	EL 6.	<b>74</b> ft.	TOC m	easure	d on mo/da	ay/yr			03/19/0	)9
		· ·	İ		test data: V										
<u> </u>			E Est. Yield		apm: V	Vell water v	vas		ft.	after		hours r	pniamu		apm
	X	-	Bore Hole	Diamete	BE USED A	in. to	10	 		ft. and		ir	n to		ft.
	sw	- sE	WELL WA	TER TO	BE USED A	S: 5 Put	lic water su	pply		8 Air co	nditioning	j 1	1 Injecti	ion well	
l <b>l</b>	i	i	1 Do	mestic	3 Feed lot	6 Oil	field water s	supply		9 Dewa	tering	1	2 Other	(Specify	below)
<i>'</i>	<u> </u>		2 Irrig	gation	4 Industria	ıl 7 Lav	vn and gard	en (do	mestic)	10 Mor	itoring we	ell			
	S				acteriological										
			submitted		J	•		•		er Well Disi		-			
TYPE OF	BLANK CAS	ING LISE			5 Wrought	Iron	8 Concre	te tile		CASING					
1 Stee			,. P (SR)		•						_ 55,110	Wek		Siempe	
		3 KM								·				Flus	·h
2 PVC					7 Fibergla										
3lank casing	diameter	Z	in. to	4.5	ft., Dia		in. te	o		ft., Dia			_in. to		ft.
Casing height	t above land	surface	Flush	i	n., weight	0.	703	lt.	bs./ft. \	Vall thickne	ess or gau	uge No.	·	SCH. 4	10
YPE OF SC	REEN OR P	EKFUKAI	ION MATERIA	NL:			L/_	PVC		10	ASDesio	os-ceme	ent		
1 Stee	4		inless steel					RMP (	SR)	11					
2 Bras		4 Gal	vanized steel					ABS			None us				
			NINGS ARE:				d wrapped			8 Saw c	ut		11 No	ne (open	hole)
	tinuous slot	_	3 Mill slot			6 Wire w	• •			9 Drilled	holes				
	ered shutter		4 Key punch			7 Torch o				10 Other	(specify)				
SCREEN-PE	RFORATED	INTERVA	LS: From		<b>4.5</b> ft	. to	9.5		_ft. Fi	rom		ft.	to		ft.
			From		ft	to			ft. Fi	rom		ft.	to		ft.
GRA	VEL PACK I	NTERVALS	S: From		3.5 ft	. to	10		_ft. F	rom		ft.	to		ft.
			From		ft	i. to			ft. F	rom		ft.	to		ft.
6 GROUT N	MATERIAL:	1 Ne	at cement	2	Cement grou	ıt	3 Ben	tonite		4 Other					
 Grout Interva	ls From	1	ft. to	3.5	ft. From		ft. 1	0	•	ft. F	rom		ft. to	D	fi
			le contaminati							ock pens					
1 Sept	•••		4 Latera		7	Pit privy				torage					
			5 Cess p												<b>/</b> )
	ertight sewer		6 Seepa			Feedyard				icide storaç			1.4.		•
Direction fron	•		10-	- •		, -			many	_	-				
FROM	ТО	CODE	L	ITHOL	OGIC LOG		FROM		0		PLUG	GING I	NTERV	ALS	
0	0.7		Concrete												
			Clay, very d	lark gr	ay brown, s	ome			T						
0.7	2		gravel				ļ								
2	5		No Recove		<u> </u>		<u> </u>	<del> </del>							
5	7.5		Clay with		ı, very dar	k gray	<b> </b>							<del></del>	
7.5	10	<del>  </del>	No Recove	ar y			<del> </del>	+							
		+					<u> </u>	+	+						
		<del>  </del>					<del>                                     </del>	+-	-+						
								+							
	· · · · · · · · · · · · · · · · · · ·	1					1	+			· · · · · · · · · · · · · · · · · · ·				
								+						······································	
		<del>   </del>					1	+	$\overline{}$						
7 CONTRA	CTOR'S OR	LANDOW	NER'S CERTI	FICATION	ON: This wat	er well was	(1) constru	cted (	2) reco	nstructed o	r (3) nluo	ged und	ler my in	risdiction :	and was
<b>—</b>				03/18		1100						_			
completed or				00/10	531					ue to the b					
			·							cord was	omple	on (mo	o/day/yr)	04/0	9/09
under the bu					al Service				ature)		1/1		S	1144-1 10	00.01::
INSTRU	CHONS: PI	ease till in bl	lanks and circle	ine come	ect answers. S	Sena three c	opies to Kans	sas Dep	parmen	t of Tealth a	ina Enviror	nment, E	sureau of	vvater, 100	30 S W