WATER	K WELL	RECORD	Form WV	VC-5	Division of Wat	er Resources App. N	0.	
		F WATER WELL:	Fraction	05	Section Number	Township No.	Range Number	
County: Allen			1/4 NE 1/4 SE		4 T 26 S R 18 ZE			
	Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:		
from	from nearest town or intersection: If at owner's address, check here .					Latitude: .37.808889 (in decimal degrees)		
MW-	MW-12					Longitude: 95.435056 (in decimal degrees)		
					Elevation:			
2 WATER WELL OWNER: Aday's Speedy Mac					Collection Method:			
RR#, Street Address, Box #: 317 S. 9th St.					GPS unit (Make/Model: Garmin 60CS			
City, State, ZIP Code : Humboldt, KS					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
		Tambor	ut, 110		Est. Accuracy: 🗸	<3 m, 🔲 3-5 m, 🗀	] 5-15 m,	
3 LOCATE WELL								
WITH AN "X" IN  4 DEPTH OF COMPLETED WELL 10							(0) -	
SECT	SECTION BOX: Depth(s) Groundwater Encountered (1)							
	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
	1	L POT VIELD		m. Well water was				
\text{VW}  \text{VC}		Pore Hole Diam	Bore Hole Diameter 8in. to .10ft. andin. toft.					
W		E   Bore Hole Diam	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
SW	V   SE -	X   Irrigation						
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well								
	S		day/yr sample was sub					
Water well disinfected? Yes V No								
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 2 in. to .5 ft., Diameter . in. to .7 ft., Diameter . ft., Diameter . ft. Line (ft., Wall thickness or gauge No., Sch. 40)								
Casing height above land surface. Flush in., Weight								
TYPE OF SCREEN OR PERFORATION MATERIAL:         □ Steel       □ Stainless Steel       □ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot								
Louvered shutter  Key punched  Wire wrapped  Saw cut  Other (specify)								
SCREEN-PERFORATED INTERVALS: From10 ft. to5 ft., From ft., From ft. to ft.								
From								
GRAVEL PACK INTERVALS: From10								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other								
Grout Intervals: From .3								
What is the nearest source of possible contamination:  Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☑ Fuel storage ☐ Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
		well		Distance	from well	-		
FROM	ТО	LITHOLOG	GIC LOG	FROM	TO LITHO. 1	LOG (cont.) or PL	UGGING INTERVALS	
0	1 (	Concrete						
1		Gravel and Sand						
3		Silty Clay						
5		Clay w/gravel and san	d					
9		Weathered Shale						
10		Boring Terminated						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .9/30/09								
Kansas Water Well Contractor's License No710 This Water Well Record was completed on (mo/day/year) .10/6/09								
under the business name of Below Ground Surface, Inc. by (signature)								
INSTRUCTIONS Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
	Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
nttp://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								