Trock	TION OF W	TED MEN	ED ACTION:	Water Well Recor	rd Form WWC-			T	
1 LOCATION OF WATER WELL:			FRACTION			Section Number	Township Number	Range Number	
Sedgwick			SW 1/4		SW 1/4	36	T 26 s	R 2E E/W	
Distance and direction frem nearest town or city street address of well if located within city?									
14818 E. 29th N. Wichita, Kansas									
WATER WELL OWNER: GEHRER, Greg									
\Box				3.7			Roard of Agriculture, D	ivivsion of Water Resource	
14010 E. 27CH N.									
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:									
	TE WELL'S " IN SECTIO	LOCATION WITH	DEPTH OF COM		80		EVATION:		
		N	Depth(s) groundwa		1	ft.	2 ft.	3 ft.	
		W	VELL'S STATIC W.	ATER LEVEL 3	5 гт	. BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	08/29/1997	
	NW	NE	Pump test	data: Well	water was	ft.	after hours pum	p ing gpm	
			st. Yield	gpm: Well	water was	ft.	after hours pum	ping gpm	
e w		E Bo	ore Hole Diameter	12 in.	to 80	ft.	and in.	to ft.	
= "		l l'Iw	ELL WATER TO E		5 Public wate	er supply		njection well	
			1 Domestic	3 Feediot	6 Oil field wa		•	Other (Specify below)	
	sw		2 Irrigation	4 Industrial	7 Lawn and g		0 Monitoring well	and (opening select)	
			•			·	· ·		
'	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was								
submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Stee	21	3 RMP (SR)		6 Asbestos-Ceme	ent 9	Other (Specify b	elow) V	Vel ded	
2 PVC		4 ABS		7 Fiberglass	S	DR-26	T	hreaded	
Blank casing Diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214									
TYPE (OF SCREE	EN OR PERFORATIO				7 PVC	10 Asbestos-ceme		
1 Stee		3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify	,	
2 Bras	19	4 Galvanized steel		6 Concrete tile		O ABS	12 None used (op	,	
			DIC ADE			ADS	8 Saw cut	•	
ŀ		RFORATION OPENI	ING ARE:		zed wrapped			11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 40 ft. to 80 ft., From ft. to ft									
			from	ft	. to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24				f	t. to 80	•		ft.	
			from	ft	. to	ft., From	ft. to	ñ.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 4 ft. to 24 ft. From						40	6 F	ft. to ft.	
What is the nearest source of possible contamination:			ia riom	14.	ft. to ft. From 10 Livestock pens		bandon water well		
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel sto			
- Lawrin Miles				8 Sewage lagoon			130	15 Oil well/Gas well	
5 Ccss poor				13 Image			addd ataman		
NOTE							n		
Direction from well? 15 How many feet?									
FROM	TO		THOLOGIC LOG		FROM	TO	PLUGGING INTER	VALS	
0 4	4	topsoil					111111111111111111111111111111111111111		
4	30	clay							
30	75	shale							
75	80	limestone							
							The state of the s		
				· · · · · · · · · · · · · · · · · · ·					
						+ +-			
			· un						
			-						
7 000	TD A COLO	DIG			4)	-1 (0)	-4-1 (0)		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
was completed on (mo/day/year)									
Under the business name of Harp Hell & Pump Service									
Under the dusiness name of AAAD									
							Joala D	. Juaro	