Linc	ATION OF W	ATER WELL:	FRACTIO	ON	Water Well R	ecord Form WW	/C-5	KSA 82a-1212	·		T	
الل								Section Number	Township Nun	nber	Range Nun	nber
Sedgwick NW 1/4 Distance and direction frem nearest town or city street address of well if loo				NE 1/4	NW 1/	4	36	т 26	<u>s</u>	R 2E	E/W	
	TER WELL		POIL, Jo			<u>Wichita</u>	ι,	Kansas				
\Box	ST. ADRESS		19 E. 3'		7				Board	of Agriculture, Di	vivsion of Water Res	ource
CITY, STATE, ZIP CODE: Wichita, Kansa									Application Number:			
LOCA	TE WELL'S I	OCATION WITH			PLETED WEL	L 12	3	ft. ELF	EVATION:	- Parenton : Tallibe		
MAN "X	" IN SECTIO	N BOX: N	Depth(s) g	roundwat	er Encountere		•	ft.	2	ft.	3	ft.
	X		WELL'S STA	TIC WA	TER LEVEL	20	FT. B	BELOW LAND SUI	RFACE MEASURED	ON mo/day/yr	08/30/2	2000
1		NE.	Pu	ımp test d	ata: We	ell water was		ft.	after	hours pum	ping	gpm
<u> </u>	1 :		Est. Yield		61	ell water was		ft.	after	hours pum	ping	gpm
Mile A	v 	E	Bore Hole Dia		12 in.		_	ft.	and	in.	to	ft.
			WELL WATE		USED AS: 3 Feedlot	5 Public w			8 Air conditioning	•	njection well	
1 1	sw		2 Irrigation		4 Industrial	6 Oil field 7 Lawn an			9 Dewatering 0 Monitoring well		other (Specify be	10W)
1			1	,,,,	ological sample				-		o/day/yr sample	wae
		S	submitted	an Buccel	orogicar sampr	c submitted to	Бер		er Well Disinfecte			was
5 TY	PE OF CA	SING USED:			5 Wrought ire	on	8 C	oncrete tile	CASING JO		lued X Clamp	oed
1 Stee	el	3 RMP (SR)			6 Asbestos-Cement 9 Other (Specify below) Welded							
2 PV	C	4 ABS			7 Fiberglass		SD	R-26		T	hreaded	
	asing Diam	•	in. to 2	4	ft., Dia		in.	to	ft., Dia	in.	to	ft.
			L2	in.,	weight	2.35			Wall thickness or		.21	4
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)												
2 Bra		4 Galvanized stee	el		6 Concrete tile 9 ABS				11 other (specify) 12 None used (open hole)			
SCREE	EN OR PEI	RFORATION OPI			5 Gauzed wrapped				8 Saw cut 11 None (open hole)			
	inous slot	3 Mill sl			6 Wire wrapped				9 Drilled holes			
2 Louve	ered shutte	r 4 Key p	unched						10 Other (spe	cify)		
SCREEN-PERFORATION INTERVALS: from 24 ft. to 123 ft., from ft. to ft.												
			fro			ft. to		ft., From		ft. to		ft.
GRAVEL PACK INTERVALS: from 24						ft. to 123	}	ft., From		ft. to		ft.
			fro			ft. to		ft., From		ft. to		ft.
	OUT MAT		cement	2 Cen	nent grout	3	Bento	onite	4 Other ber	tonite	hole pl	Lug
Grout Intervals: From ft. to What is the nearest source of possible contamination:					ft. From ft			to ft. Fro 10 Livestock pens				
1 Septic tank 4 Lateral lines					7 Pit privy			11 Fuel storage		14 Abandon water well		
2 Sewer lines 5 Cess pool					8 Sewage l	-		12 Fertilizer storage		15 Oil well/Gas well 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit					9 Feedyard			13 Insection	cide storage	None Apparent		
Directio	n from we	-			•				How many feet?			
FROM			LITHOLOGIC	LOG		FRO	И	TO		GING INTER	VALS	
0	4	topsoil					_					
10	10 123	clay shale &	1									
10	143	snare «	limesto	ne								
							_					
			.,		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,							
		1111-1-11										
							_					
							_					
-												
							-					
						****	-					
7	MTD A COTO	Dicor	n.a.a			- (d) 1		(0) ====================================	101 - 101 - 1			
		R'S OR LANDOWNE on (mo/day/year										
		on (mo/day/year 's License No										
Under	the busin	ness name of.从名	rp Well	&. P	ump Ser	vice,	Inc	by (sign	aturo)		_	
1									•	roaa S	S. Harp	