

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number		Range Number	
County: Sedgewick		C 1/4 SE 1/4 NE 1/4	27		T 24 S		R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 4255 N. 127th St. E., Wichita								
2 WATER WELL OWNER: Kirk Holliday								
RR#, St. Address, Box # : 4255 N. 127th St. E.						Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, KS 67226						Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 90 ft. ELEVATION:					
			Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 9-10-02 WELL'S STATIC WATER LEVEL 40 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No								
5 TYPE OF BLANK CASING USED:								
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded								
Blank casing diameter 5 in. to 50 ft. Dia in. to ft. Dia in. to ft.			Threaded					
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. SDR 26								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement								
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 2 Mill slot 3 Wire wrapped 6 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From 50 ft. to 90 ft. From ft. to ft. From ft. to ft. From ft. to ft.								
GRAVEL PACK INTERVALS: From 20 ft. to 90 ft. From ft. to ft. From ft. to ft. From ft. to ft.								
6 GROUT MATERIAL:								
1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout intervals: From 4 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)								
Direction from well? How many feet?								
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0 23 clay								
23 36 shale								
36 38 lime								
38 65 shale								
65 82 shale w/ lime streaks								
82 90 lime & cherty lime								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-10-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 171 This Water Well Record was completed on (mo/day/yr) 9-18-02 under the business name of G+S Drilling Inc. by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATERWELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.								