Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER FRACTION Sedgwick NE NW26 2ENE 36 S R É/W 1/4 1/4 1/4 Т Distance and direction from nearest town or city street address of well if located within city? 13425 E. 37th N. Wichita, Kansas WHEELER, Steve WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 13425 E. 37th N. Wichita, Kansas CITY, STATE: Application Number: ZIP CODE 65 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft Depth of groundwater Encountered: ft. Ν 25 WELL'S STATIC WATER LEVEL 3/25/03 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW. NE-Est. Yield: ft. after hours of pumping @ gpm Well water was Φ gpm 12 to 65 ft. Ξ Bore Hole Diameter and WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE-3. Feedlot 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample NO Was a chemical/bacteriological sample submitted to Department? YES (YES) Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6 Ashestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Blank casing diameter 45 ft., Dia. Dia ft. Casing height above land surface: 2.35 in. Weight: lbs / ft Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 3. Stainless Steel 1. Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 10. Other (specify) 8. Saw cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 65 SCREEN - PERFORATION INTERVAL 45 ft ft., From to From ft. ft to From From ft.. to ft. 24 65 GRAVEL PACK INTERVALS: to From ft., From to ft. From ft. to ft., From ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. ft.. From ft ft From ft to What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 7. Pit privy 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? North How many feet? 30 LITHOLOGIC LOG LITHOLOGIC LOG From Τо From To topsoil clav 47 brown shale 47 grev shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged

was completed on (mo/day/year)

Was Sometime of 1

Was constructed 2. Teconstructed 3. progress of the constructed 3. progre