WATER WELL RECORD F	orm WWC-5 KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER	
Sedgwick NW 1/4 SE 1/4 NE Distance and direction from nearest town or city street address of well if located within city?	1/4 34 T 26 S R 2E E/W	
12400 Four Oaks Wichita, Kansas		
2 WATER WELL OWNER: LOWERY, Lisa		
RR#,ST. ADDRESS,BOX #: 12400 Four Oaks	Board of Agriculture, Division of Water Resource	
CITY, STATE: Wichita, Kansas 3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 80	ZIP CODE: Application Number:	
WITH AN "X" IN SECTION BOX:		
N Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 40	ft. ft. ft. ft. ft. ft. ft. st. ft. ft. ft. ft. ft. ft. ft. ft. ft. f	
	9Fm	
Est. Yield: gpm Well war Bore Hole Diameter 12 in.	to 85 ft. and in. to ft.	
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public wa	ter supply 7. Lawn and garden only 9. Dewatering 11. Injection well 12. Other (Specify below)	
	ater supply 8. Air conditioning 10. Monitoring well	
S Was a chemical/bacteriological sample submitted to D	Department? YES NO ; If yes, what mo/day/yr was sample	
submitted TYPE OF CASING USED:	Was Water Well Disinfected? YES NO	
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR)	9. Other (Specify below) CASING JOINTS: Glued Threaded CDP 26 Welded Clamped	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete ti		
Blank casing diameter 5 in. to 40 ft., Dia.	in. to ft., Dia. in. to ft.	
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft. Wall thickness or gauge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:	44 Ohns (2001)	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	9. ABS 11. Other (specify)	
	10. Asbestos-Cement 12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut 9. Drilled holes 11. None (open hole)	
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify)	
40	90 -	
SCREEN - PERFORATION INTERVAL From 40 ft. to	80 ft., From ft. to ft.	
. From ft. to GRAVEL PACK INTERVALS: From 24 ft. to	ft., From ft. to ft. 80 ft., From ft. to ft	
From ft. to	A	
CROUT MATERIALS:	11. (0 1).	
Grout Intervals: 1. Neat cement 2. Cement Grout Grout Intervals: From 4 ft. to 24 ft., From	3. Bentonite Other bentonite hole plug ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:		
1. Septic tank 4. Lateral lines	16 Other (annuity balance)	
2. Sewer lines 0. Good root	Fuel storage 14. Abandon water well 16. Other (specify below) 2. Fertilizer storage	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1 Direction from well? Southeast	How many feet? 100	
From To LITHOLOGIC LOG	From To LITHOLOGIC LOG	
0 4 topsoil		
4 18 clay		
18 80 shale		
Contractor's or Landowner's Certification: This water well was 1, constructed		
was completed on (mo/day/year) 12-14-2004 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/17/2004		
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp		