

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 SW 1/4 NW 1/4		SECTION NUMBER 19	TOWNSHIP NUMBER T 26 S		RANGE NUMBER R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 5144 Colonial Ave. Bel Aire, Kansas								
2 WATER WELL OWNER: HOOFER, David		Board of Agriculture, Division of Water Resource						
RR#,ST. ADDRESS,BOX #: 5144 Colonial Ave.		Application Number:						
CITY, STATE: Bel Aire, Kansas		ZIP CODE:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 122 ft. ELEVATION:						
1 Mile N W E S		Depth of groundwater Encountered: ft.						
		WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 2/23/06						
		Pump test data: Well water was ft. after hours of pumping @ gpm						
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm						
		Bore Hole Diameter 12 in. to 122 ft. and in. to ft.						
WELL WATER TO BE USED AS:		9. Dewatering 11. Injection well						
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)								
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted		Was Water Well Disinfected? YES NO						
5 TYPE OF CASING USED:		CASING JOINTS: Glued Threaded						
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)		Welded Clamped						
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26								
Blank casing diameter 5 in. to 24 ft., Dia. in. to ft., Dia. in. to ft.								
Casing height above land surface: 24 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214								
TYPE OF SCREEN OR PERFORATION MATERIAL:		11. Other (specify)						
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 12. None used (open hole)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement								
SCREEN OR PERFORATION OPENINGS ARE:		11. None (open hole)						
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes		10. Other (specify)						
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut								
SCREEN - PERFORATION INTERVAL From 24 ft. to 122 ft., From ft. to ft., From ft. to ft.								
GRAVEL PACK INTERVALS: From 24 ft. to 122 ft., From ft. to ft., From ft. to ft.								
6 GROUT MATERIALS:		Other bentonite hole plug						
1. Neat cement 2. Cement Grout 3. Bentonite								
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:		15. Oil well/Gas well						
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage		16. Other (specify below)						
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? North		How many feet? 12 feet plus						
From To LITHOLOGIC LOG		From To LITHOLOGIC LOG						
0	3	topsoil						
3	7	clay						
7	17	fine sand and sandy clay						
17	45	tan shale/limestone						
45	50	red shale						
50	121	gray shale						
121	122	limestone						
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 2/23/2006 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/27/2006								
under the business name of Harp Well & Pump Service Inc. by (signature) <i>Jo d d S. Harp</i>								