	WATER WELL RECO	RD Form WW	C-5 KSA 82a-12	212	
1 LOCATION OF WATER WELL:	FRACTION	SECTI		HIP NUMBER	RANGE NUMBER
Sedgwick Sedgwick	SE 1/4 NW 1/4	NW 1/4	12 T	26 s	R 2E E/W
	own or city street address of well if located within ci	ity?			
6700 N. 143rd St.	Wichita, Kansas	7.00			
2 WATER WELL OWNER:	DEFFENBAUGH BUILDING	. CO.		Board of Agric	ulture, Division of Water Resource
RR#,ST. ADDRESS,BOX #:	7240 N. 143rd E.		67228	_	
CITY, STATE:	Wichita, Kansas		CODE: 67228	Application Numb	ber:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX	4 DEPTH OF COMPLETED WELL:		ELEVATION		
N	Depth of groundwater Encountered:	ft.		ft.	ft.
	WELL'S STATIC WATER LEVEL	20 FT. BELOV	V LAND SURFACE MEA	SURED ON mo/da	ay/yr: 4/29/10
- NW NE	Pump test data:	Well water was	ft. after	hours	of pumping @ gpm
w Wile	Est. Yield: gpm	Well water was	ft. after		of pumping @ gpm
₹ w		n. to 5 5	ft. and	in.	to ft.
Sw sE	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5.	Public water supply	7. Lawn and garden o	9. Dewaterin	•
		Oil field water supply		10. Monitoring	12. Other (Specify below)
S	Was a chemical/bacteriological sample si		YES (NO)		hat mo/day/yr was sample
	submitted		Was Water Well Dis	infected?	YES NO
5 TYPE OF CASING USE	5 Wrought Iron /	Fiberglass 9. Oth	ner (Specify below) C	ASING JOINTS: 🤇	Glued Threaded
	RPM (SR)	Concrete tile SDR	-26		Welded Clamped
	. AB3	Concrete tile			
Blank casing diameter	5 in. to 40 ft.,	Dia. in.	to ft.,	Dia. ir	n. to ft.
Casing height above land surf	face: 12 in., $ ext{W}$	/eight: 2.35 lbs	s. / ft. Wall	thickness or gauge	e No214
TYPE OF SCREEN OR PERF		200		Oth (:6-)	
1. Steel 3. Stainles		9. AB		Other (specify)	-1-1
2. Brass 4. Galvani:	zed 6. Concrete Tile 8. F	RMP (SR) 10. As	bestos-Cement 12.	None used (open h	10le)
SCREEN OR PERFORATION					
1. Continuous slot	3. Mill slot 5. Gauzed wrappe	d 7. Toro	ch cut 9. Di	illed holes	11. None (open hole)
2. Louvered shutter	4. Key punched 6. Wire wrapped	8. Saw	/ cut 10. O	ther (specify)	
SCREEN - PERFORATION INT	TERVAL From 40 ft.	to 55	ft., From	ft.	to ft.
	From ft.	to	ft., From	ft.	to ft.
GRAVEL PACK INTER	RVALS: From 24 ft.	to 55	ft., From	ft.	to ft.
	From ft.	to	ft., From		-
6 GROUT MATERIALS:				ft.	to ft.
[1. Neat cement 2. Cement G	_	Bentonite		onite hole plug
Grout Intervals: From What is the nearest source of n	35 ft. to 40 ft.,	From ft.	to ft.,	From 4	ft. to 24 ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well					
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent					
Direction from well?			How	many feet?	
From To	LITHOLOGIC LOG	From	То	LITHOLO	GIC LOG
0 4 fill dir	t				
4 15 clay					
	reaks of fine sand				
30 55 grey sl	nale				
					,
					V V
			i		
7 Contractor's or Landowne	r's Certification: This water wall was 1	onstructed 2 rec	onstructed or 3	plugged	nder my jurisdiction and
\vdash	4/00/0010		onstructed or 3.		nder my jurisdiction and
was completed on (mo/day/y	ear) 4/29/2010 and t	his record is true to the l	best of my knowledge an	d belief.	
was completed on (mo/day/y Kansas Water Well Contracto	ear) 4/29/2010 and t	his record is true to the l	best of my knowledge an completed on (mo/day/y	d belief.	2010