WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SW12 26 Т **2E** 1/4 S F/W Distance and direction from nearest town or city street address of well if located within city? 6600 N. 143rd St. E. Wichita, Kansas RYAN DEFFENBAUGH BUILDING CO. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 7240 N. 143rd E. Wichita, Kansas CITY, STATE: ZIP CODE 97 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION ft. WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. 30 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 4/22/10 Pump test data: Well water was ft. after hours of pumping @ -MW NE apm Est. Yield: Well water was Φ apm ft. after hours of pumping @ gpm Ž 12 97 Bore Hole Diameter in. and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 8. Air conditioning 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 37 Dia. in. to in ft... Dia. ft tο in to 12 Casing height above land surface: in.. Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 9. ABS 11. Other (specify) 1. Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 9. Drilled holes 11. None (open hole) 1. Continuous slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL ft. From to ft.. From ft. From ft. to ft.. From ft. GRAVEL PACK INTERVALS: 24 to From ft.. ft From ft. From ft to ft., From ft. GROUT MATERIALS Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. 24 ft., ft. ft. to ft.. From What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 5. Cess Pool 14. Abandon water well 2. Sewer lines None Yet 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? LITHOLOGIC LOG From To From To LITHOLOGIC LOG 0 4 topsoil 4 15 clay 15 80 shale 80 97 shale and lime under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed plugged was completed on (mo/day/year) 4/22/2010 and this record is true to the best of my knowledge and belief.

4/23/2010

Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

This water well record was completed on (mo/day/year) by (signature)

Todd S. Harb