			WATER WE	ELL RE	CORD	Fo	rm WW	C-5 K	(SA 82a-12	12		
1 LOCATION OF WATER WELL: FRACTION							ON NUMBE	1	P NUMBER	RANGE N		
Sedgwick NW 1/4 NE 1/4 SE Distance and direction from nearest town or city street address of well if located within city?						1	1/4	25	Т 2	6 S	R 21	E E/W
45th St. N. and 159th E., 1/2 mile S., West to job Wichita, Kansas												
	WELL O		FFENBACH, R				** 101110	, 1141154				
ightharpoonup	DDRESS,BOX #: 15400 E. Evening Shade Board of Agriculture, Division of Water Resonance Board of Board o											Water Resource
	CITY, S	TATE: Wic	chita, Kansas				ZIF	CODE:		Application Nun	nber:	
3 LOCATE W	VELL'S LOC	CATION 4	DEPTH OF COMPI	LETED W	ELL:	130	ft.		ELEVATION:			
WITHAN	N N	Do	epth of groundwater	Encounte	red:		ft.			ft.		ft.
		' V	VELL'S STATIC WA	TER LEVE				N LAND S	URFACE MEAS	JRED ON mo/o	lay/yr: 12/2	27/10
MA	*	- NE		np test dat					ft. after		of pumping @	gpm
w N			Est. Yield: Bore Hole Diameter	gpm 12		water	was to 10	00 ft	ft. after and	hours in.	s of pumping @ to	gpm ft.
2 "		X	VELL WATER TO B				10 1	00 n	. and		44 1.1	ection well
sv	w	SE 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify belows)										
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted was Water Well Disinfected? YES NO												
5 TYPE OF CASING LISED: CASING JOINTS: Clied Threaded												
1. Steel 3. RPM (SR) Welded Clamped												
2. P		4. ABS	6. Asbestos		8. Concret	e tile						
Blank casing	g diameter	5	44	40 ft.,	Dia.	_	in.	to	ft.,	Dia.	in. to	ft.
	•	land surface:	12 in.,		Weight:	2.	.35 lb	s. / ft.	Wall th	nickness or gaug	ge No214	ŀ
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)												
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
1. Continue		3. Mill s		Sauzed wi	rapped		7. Tor	ch cut	9. Dri l	led holes	11. None (open hole)
SCREEN - PE	ERFORA	TION INTERVAL		40	ft.	to	130	ft.,	From	ft.	to	ft.
0.00		N/ WITED\/A\ 0	From	24	ft. ft.	to	130	ft.,	From	ft.	to	ft.
GRA	AVEL PAC	K INTERVALS:	From	24		to	130	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.
Paul 1 7 1 24 7 7									tonite hole pl	J		
What is the pearest source of possible contamination:									From	ft. to		
1. Septic ta		•	ral lines 7.	. Pit privy		10.	Livestoci	k pens	13. Insect	ticide storage	15. Oil well/	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify												
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									None a	pparent		
Direction from			LITUOLOGIC			_		T-	How m	any feet?	2010 1 00	
From	To 3	topsoil	LITHOLOGIC	LOG		+	From	То		LITHOLO	OGIC LOG	
3		clav										
20	80	gray shale				\Box						
80		limestone				+			<u> </u>			
86		gray shale				-+						
95 110		limestone gray shale				_						
		6V										
						\dashv						
						\dashv						
						\dashv						
						-						
					_	ㅗ						
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and												ction and
was completed on (mo/day/year) 12/27/2010 and this record is true to the best of my knowledge and belief.												
Kansas Wa	ater Well	Contractor's Lice	ense No. 236		This water	r well	record wa	s complete	d on (mo/day/ye	ar) 12/2	9/2010	
under the b	business i	name of Harp	p Well and Pun	np Serv	ice		by (sig	gnature)	Τ	odd S	. Hart)