WATER WELL RECORD Form W				VWC-5	Di	vision of Water	r Resources App. No	0.		
1 LOCATION OF WATER WELL:			Fraction				Township No.	Range Number		
County: Sedgwick		1/4 NW 1/4 NE			34	T 26 S				
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:										
from nearest town or intersection: If at owner's address, check here										
12501 E. 37th St. N.						Longitude: (in decimal degrees) Elevation:				
Wichita, KS 67228						Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27				
2 WATER WELL OWNER: DB Construction						Collection Method:				
RR#, Street Address, Box #: 15307 E. 71st South						GPS unit (Make/Model:)				
City	, State, Z	ZIP Code : Derby, k	(S 67037	3 67037			Digital Map/Photo, Topographic Map, Land Survey			
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m										
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 98 ft.									
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1).75 ft. (2) ft. (3) ft.									
	WELL'S STATIC WATER LEVEL25ft. below land surface measured on mo/day/yr									
	Pump test data: Well water was									
EST. YIELD. 30 gpm. Well water was ft. after hours pumping gpm										
W E Bore Hole Diameter 1.0										
SWSE										
Was a chemical/bacteriological sample submitted to Department? \(\subseteq \text{Yes} \) No										
S If yes, mo/day/yr sample was submitted										
1 mile Water well disinfected? ☐ Yes ☑ No										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: Of Glued Clamped Welded Threaded										
Casing diameter .5." in. to										
Casing height above land surface. 12" in., Weight .160 lbs./ft., Wall thickness or gauge No.										
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)										
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)										
SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)										
Louvered shutter										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From 20' ft. to 98 ft., From ft. to ft.										
From										
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout										
Grout Intervals: From .5										
What is the nearest source of possible contamination:										
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well										
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well										
		طلاب م	····			eii50.+				
FROM		LITHOLOG	IC LOG	FROM	TO	LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS		
0	4	earth								
4	15	clay				***************************************				
15 30	30 40	shale		 						
40	98	red clay shaley lime								
40	130	Shaley little		-						
	† 			++						
			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged										
under my jurisdiction and was completed on (mo/day/year) .2/12/13 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/year) Policense No. 493										
under the business name of Reiserer Well Drilling by (signature)										
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.										
Telephon	e 785-296-	5524. Send one copy to WAT								
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy										
110/1 0/2	. 1212				Ch	ICCK. WI	пс сору, 🗀 ви	ь сору, 🗀 тык сору		