WATER WELL RECORD FO	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NE 1/4 NE 1/4 NW	1/4 34	T 26 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?			
11511 E. Winston Wichita, Kansas			
2 WATER WELL OWNER: NIES HOMES			
RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. #303			iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE: 6'	7206 Application Nur	nber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 86		ELEVATION:	
WITH AN "X" IN SECTION BOX:		ft.	ft.
Depth of groundwater Encountered:	ft.		
WELL'S STATIC WATER LEVEL 36	FT. BELOW LAND SU	PREACE MEASURED ON mo/	
Pump test data: Well water	er was	ft. after hour	s of pumping @ gpm
<u>υ</u> ' Est. Yield: gpm Well water		ft. after hour	s of pumping @ gpm
Est. Yield: gpm Well water  Bore Hole Diameter 12 in.	to <b>86</b> ft.	and in.	to ft.
₩ELL WATER TO BE USED AS:		9. Dewater	ing 11. Injection well
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)			
2. Irrigation 4. Industrial 6. Oil field wa	ater supply 8. Air con	. 16	•
S Was a chemical/bacteriological sample submitted to D			what mo/day/yr was sample YES NO
submitted	Was v	Vater Well Disinfected?	TES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	<ol><li>Other (Specify</li></ol>	below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR)	SDR-26		Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete til	e 5-11-1		
Blank casing diameter 5 in. to 40 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.23 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:		_	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer	ment 12. None used (oper	hole)
, ,			•
SCREEN OR PERFORATION OPENINGS ARE:			44 None ( annu bala)
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 40 ft. to	86 ft.,	From ft.	to ft.
		_	
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	<b>86</b> ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other ben	tonite hole plug
2. Sometime State Property of the Property of			
Grout Intervals: From ft. to ft., From ft. to ft., From 4 ft. to 24 ft.  What is the nearest source of possible contamination:			
1. Septic tank 4. Lateral lines 7. Pit privy 1	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
40 Fullbandon			
Valentight sower miles			
	From To		
From To LITHOLOGIC LOG	From To	LITHOL	OGIC LOG
0 3 topsoil			
3 45 brown shale			
45 80 gray shale			
80 86 limestone			
	<del> </del>		
	<del>                                     </del>		· · · · · · · · · · · · · · · · · · ·
	<del>  </del>		
	<del>                                     </del>		
	1		
7			under my bullediation and
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 3/28/19 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/29/19			
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp			