		WATER W	/ELL RE	CORD F	orm WV	VC-5 K	SA 82a-12	12		
1 LOCATION OF WATER	WELL:	FRACTION			SEC	TION NUMBER	L.	IIP NUMBER	RANGE NU	
Sedgwick		SE 1/4		1/4 NW	1/4	34	T	26 S	R 2E	E/W
Distance and direction from		treet address of we	ell if located wi		Zancac					
2 WATER WELL OF RR#,ST. ADDRESS,I	WNER: <b>ROB</b> BOX #: <b>5842</b>	L CONSTR W. 21st N. ita, Kansas	UCTION	Wichita, I		P CODE: 6	7205	Board of Agri	culture, Division of W	ater Resource
3 LOCATE WELL'S LOC		EPTH OF COM	PLETED WI	FIL: 9		F CODE	ELEVATION:	, фриоздол та		
WITH AN "X" IN SECT	TION BOX:	th of groundwate			ft.			ft.		ft.
NW		LL'S STATIC W		EL 30		W LAND SL	IRFACE MEAS ft. after	SURED ON mo/d hours	lay/yr: 7/30 of pumping @	/ <b>19</b> gpm
w Z	'	Est. Yield:	gpm	Well wa		\ <del>-</del>	ft, after		of pumping @	gpm
Σ w	'   1	ore Hole Diamete LL WATER TO			to 9	<b>95</b> ft.	and	in.	to	ft. tion well
sw -			S. Feedlot	.o. 5. <b>Public w</b> a	ter supply	7. Lawn a	ınd garden on	9. Dewateri	ng 12. Other (Sp	
s	w	Irrigation 4 as a chemical/bactoritted		6. Oil field v		YES	ditioning NO Vater Well Disi		what mo/day/yr w	ras sample
5 TYPE OF CASI	NG USED:	5. Wrough	at Iron	7. Fiberglass	9. O	ther (Specify	below) CA	SING JOINTS: (	Glued	Threaded
1. Steel 2. PVC	3. RPM (SR 4. ABS	3)	os-Cement	8. Concrete	GD.	R-26	,		Welded	Clamped
Blank casing diameter	r <b>5</b> i	in. to	30 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above		12 in.,		Weight:	2.35	bs. / ft.	Wall	thickness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cernent 12. None used (open hole)										
SCREEN OR PERFOR	RATION OPENING	S ARE:								
1. Continuous slot	3. Mill slo	<b>x</b> 5.	Gauzed wr	apped	7. <b>To</b>	rch cut	9. <b>D</b> ri	illed holes	11. None ( o	pen hole)
2. Louvered shutter	4. Key pu	ınched 6.	Wire wrap	ped	8. Sa	w cut	10. Ot	her (specify)		
SCREEN - PERFORAT	TION INTERVAL	From	30	ft. to	95	ft.,	From	ft.	to	ft.
		From		ft. to	)	ft.,	From	ft.	to	ft.
GRAVEL PAC	K INTERVALS:	From	24	ft. t	95	ft.,	From	ft.	to	ft.
		From		ft. te	<b>o</b>	ft.,	From	ft.	to	ft.
6 GROUT MATERIA	ALS: 1. Neat o	ement	2. Cem	ent Grout		3. Bentonite		Other bent	onite hole plu	ıg
Grout Intervals:	Grout Intervals: From ft. to ft., From ft. to ft., From 4 ft. to 24									<b>24</b> ft.
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy  10. Livestock pens  13. Insecticide storage  15. Oil well/Gas we								as well		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (speci								ecify below)		
③ Watertight sewer	line 6. Seepag	ge pit	9. Feed yar	d	12. Fertilize	r storage				
Direction from well?	Southwe						How r	nany feet? 80 f		
From To		LITHOLOGI	C LOG		From	То		LITHOLO	GIC LOG	
	topsoil clay				+					
	brown shale									
52 95	grey shale				<del>.  </del>	<u> </u>				
					<del> </del>					
	,				<b> </b>					
					+					
7 Contractor's or l	andowner's Certific	cation: This water	r well was 1	constructe	d) 2, re	constructed	d or 3.	plugged	under my jurisdicti	ion and
was completed on (		7/30/19		and this record					••	
Kansas Water Well						-	I on (mo/day/ye		1/19	
under the business			mp Serv			ignature)			. Harp	ı