


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Sedgwick	Fraction 1/4 1/4 NW 1/4	Section number 24	Township number T 26 S R 2 E	Range number 2 E
2. Distance and direction from nearest town or city: Street address of well location if in city:		3/2 mi SW of Benton		3. Owner of well: R.R. or street: City, state, zip code:		
				Betty Lickteig Wichita Kans		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 10 in. Completion date 11-20-1976 Well depth 68 ft.		
		well in wheat field		7. <input checked="" type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
5. Type and color of material		From		To		8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
						9. Casing: Material galv Height: above or below Threaded <input type="checkbox"/> Welded gl Surface 16 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 17.5 lbs./ft. Dia. 6 in. to 68 ft. depth Wall Thickness: inches or Dia. 1/2 in. to 17.5 ft. depth gage No. 17.5
						10. Screen: Manufacturer's name gt Z Type RMP Dia. 6 in <input checked="" type="checkbox"/> Slotted gauze 1/4 Length 20 ft Set between 40 ft. and 60 ft. ft. and 60 ft. Gravel pack? no Size range of material 20-40
						11. Static water level: 35 ft. below land surface Date 11-19-1976 mo./day/yr.
						12. Pumping level below land surfaces: ft. after 10 hrs. pumping 10 g.p.m. ft. after 10 hrs. pumping 10 g.p.m. Estimated maximum yield 10 g.p.m.
						13. Water sample submitted: 10 mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date 11-19-1976
						14. Well head completion: Pitless adapter 16 inches above grade
						15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: ft. 0 Direction SW Type SW Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
						17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Wike well drilling Model number 122 HP 1/2 Volts 115 Length of drop pipe 10 ft. capacity 10 g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
18. Elevation:		19. Remarks:		20. Water well contractor's certification:		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		owner will put on slab B. J. Lickteig		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Wike well drilling 122 Business name Augusta Kans License No. 11-201976 Address Wichita Kans Signed Murray Wike Date 11-20-1976 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5