				R WELL RECORD	Form WWC-5	KSA 82a			
	ON OF WAT	ER WELL:	Fraction			tion Number	Township Number	Range Number	
County:	Sedgw		SE 1/2		SE 1/4	31	T 26 S	R 2 (B)W	
			•	address of well if located	-		50895014		
				et North & Rock Ro			AmocoNo. 2316	MW-5	
2 WATE	R WELL OW	NER: Ground	water Manage	ment Section, Amoc	o Oll Compa	any			
RR#, St. /	Address, Bo	<# : ₹ 7201 E	• 38th Stree	et, Space 7253			Board of Agriculture	, Division of Water Resources	
		: Tulsa,			Application Number:				
3 LOCAT	E WELL'S L						TION: Approx. Surfa		
		1 1	- Depth(s) Ground	water Encountered 1.	NONE	ft. 2	ft.	3	
ŢΓ	!	I 1	WELL'S STATIC	WATER LEVEL	9•0 ft. be	olow land surf	ace measured on mo/day/y	n 02/16/89	
	1	NE	Pum	p test data: Well water	was	ft.af	ter hours p	pumping gpm	
	1		Est. Yield	A	was	ft.af	ter hours p	oumping gpm	
.≝ w -	i		Bore Hole Diameter					in. toft.	
w w	1	1	WELL WATER			8 Air conditioning 11 Injection well			
7 ·	- sw	SEX	1 Domestic	3 Feedlot 6	6 Oil field wat	er supply	9 Dewatering 12	2 Other (Specify below)	
			2 Irrigation	A local stated		and an amb a	Monitoring wall		
	i		Was a chemical/	bacteriological sample si	ubmitted to De	partment? Ye	s; If ye	s, mo/day/yr sample was sub	
1 -		r	mitted			Wat	er Well Disinfected? Yes	No X	
5 TYPE C	OF BLANK C	ASING USED:		5 Wrought iron	8 Concre	te tile	CASING JOINTS: Glu	ed Clamped	
1 St	eel	3 RMP (SR)	)	6 Asbestos-Cement	9 Other (	specify below		lded	
(2PV		4 ABS		7 Fiberglass				eadedX	
								. in. to	
Casing he	ight above la	ind surface	2	.in., weight		Ibs./f	t. Wall thickness or gauge	No. Schedule 40	
TYPE OF	SCREEN O	R PERFORATION	MATERIAL:				10 Asbestos-cen	nent	
1 Ste	eel	3 Stainless	steel	5 Fiberglass	8 RM	P (SR)	11 Other (specify	y)	
2 Bra	ass	4 Galvanize	d steel	6 Concrete tile	9 ABS	6	12 None used (d	open hole)	
SCREEN	OR PERFOR	RATION OPENING	S ARE:	5 Gauze	d wrapped		8 Saw cut	11 None (open hole)	
1 Co	ontinuous slo	t <b>3</b> Mill	slot	6 Wire w	rapped		9 Drilled holes		
2 Lo	uvered shutt	er 4 Key	y punched	7 Torch	cut		10 Other (specify)		
SCREEN-	PERFORATE	D INTERVALS:	From			ft., Fron	nft.	toft.	
			From	ft. to		ft., Fron	nft.	toft.	
(	GRAVEL PA	CK INTERVALS:	From			ft., From	n ft.	toft.	
			From	ft. to		ft., Fron	n ft.	to ft.	
	T MATERIAL	: 1 Neat ce	ement (	Cement grout	Bentor	nite 4	Other		
Grout Inter	rvals: From	nf	t. to	ft., From 4.	ft. t	o6	ft., From	ft. to	
What is th	e nearest so	urce of possible c	ontamination:			10 Livest	ock pens 14	Abandoned water well	
1 Se	eptic tank	4 Lateral	l lines	7 Pit privy		DFuel s	torage 15	Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon 12 Fe		12 Fertiliz	ertilizer storage 16 Other (specify below)		
3 W	atertight sew	er lines 6 Seepa	ge pit	9 Feedyard		13 Insect	icide storage		
Direction f	rom well?	WNW				How man	y feet? 113		
FROM	TO		LITHOLOGIC	LOG	FROM	то	PLUGGING	INTERVALS	
0	5.5	Brown Lean S	ilty Clay						
5.5	11	Olive-Brown	Lean to Fat	Silty Clay					
11	16	011ve-Green	Fat to Lean	Clay					
16	17	Olive-Green	Highly Weath	nered Shale					
							······································		
		1. m. 1. m					an all tan so un se		
			1. cr	······					
						L_		dos mu insiediation and	
								nder my jurisdiction and was	
completed	on (mo/day/	year)	A16					nowledge and belief. Kansas	
	Contractor				Hecord was	s completed o	on (mo/day/yr// <i>3.7.</i>	Q. J. Q . I /	
Lundor the		. –	A	Landa las					
	business na		acon Consul			by (signat		anich	
					ase fill in blanks, u		ure) the correct applied send top three WELL OWNER and retain one for	copies to Kansar Department	