			WATER	WELL RECORD	Form WWC-5	KSA 82a-	1212	
	ION OF WA	TER WELL:	Fraction	ME		tion Number	Township Number	Range Number
	Sedgwick		SE 1/4		SE 1/4	31	T 26 S	R ² (E)W
			-	dress of well if located North & Rock Rd.	-	KS	50895014	MW-2
	R WELL OW			ent Section, Amoc			Amoco No. 2316	
_			, 38th Street,		O OTT COMP	illy	Decad of Assicultura	Division of Water Becourse
	Address, Bo e, ZIP Code		OK 74145	Space 7255	Board of Agriculture, Division of Water Resources Application Number:			
LOCAT	E WELL'S L	OCATION WITH		MPLETED WELL	21	ft. ELEVAT	TION: Approx. Surfa	
3 AN "X"	' IN SECTIO	N BOX:	Depth(s) Groundw	ater Encountered 1	10	ft. 2	ft.	3
ī [ı	,	WELL'S STATIC	WATER LEVEL	8•3 ft. b	elow land surf	ace measured on mo/day/y	_{/r} 02/16/89
	1							oumping gpm
	NW	NE	•				-	oumping gpm
ا ف	i		Bore Hole Diamet	er9in. to	21.5	ft., a	ın d	in. to
* w	1		WELL WATER TO	D BE USED AS:	5 Public wate	r supply	8 Air conditioning 1	1 Injection well
7 l	sw	SE -X	1 Domestic	3 Feedlot	6 Oil field wat	er supply	9 Dewatering 12	2 Other (Specify below)
l ľ	347		2 Irrigation					
l L	i		Was a chemical/ba	acteriological sample s	ubmitted to De	epartment? Ye	s; If y∈	es, mo/day/yr sample was sub
<u> </u>			mitted			Wat	er Well Disinfected? Yes	No X
5 TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 Concre	te tile	CASING JOINTS: Glu	ed Clamped
1 St	teel	3 RMP (SR)	6 Asbestos-Cement	9 Other	specify below) We	lded
3 P\		4 ABS		7 Fiberglass				eadedX
Blank cas	ing diameter	i	n. to 6	ft., Dia	in. to		ft., Dia	. in. to ft.
							t. Wall thickness or gauge	
TYPE OF	SCREEN O	R PERFORATION	MATERIAL:		P VO	0	10 Asbestos-cer	nent
1 St	teel	3 Stainless	steel	5 Fiberglass	8 RM	P (SR)	11 Other (specif	y)
2 Br	rass	4 Galvanize	d steel	6 Concrete tile	9 AB	3	12 None used (d	open hole)
SCREEN	OR PERFOR	RATION OPENING	S ARE:	5 Gauze	d wrapped		8 Saw cut	11 None (open hole)
1 C	ontinuous slo	ot 3 Mill	slot	6 Wire v	wrapped		9 Drilled holes	
2 Lo	ouvered shut	ter 4 Key	y punched	7 Torch			10 Other (specify)	
SCREEN-	PERFORATI	ED INTERVALS:	From 6.	ft. to	21	ft., From	1 ft.	toft.
				ft. to		ft., From	ı ft.	to
(GRAVEL PA	CK INTERVALS:	From 5	.5 ft. to	21.5	ft., From	1 ft.	toft.
+			From	ft. to		ft., From	n ft.	to ft.
3] GROU	T MATERIAL			Cement grout	Bentor	nite4 (
Grout Inte		m		ft., From3.	ft. 1	to	ft., From	ft. toft.
		ource of possible o				10 Livesto	•	Abandoned water well
•		4 Lateral		7 Pit privy		→ Fuel s	torage 15	Oil well/Gas well
		5 Cess p		8 Sewage lago	on		<u> </u>	Other (specify below)
	_	er lines 6 Seepa	ge pit	9 Feedyard			_	
_	from well?	SSW					y feet? 12	
FROM 0	4.5	Cray-Brown L	LITHOLOGIC L ean Silty Clay		FROM	то	PLUGGING	INTERVALS
4.5	9.5		o Fat Silty Clay		 			
9.5	14.5			lay				
14.5	21.5	Olive-Green		.l. Usadhamad Cha	.L.		J	
14.5	21.0	UTIVE-Green I	ai Clay (High	nly Weathered Sha				
	-							
	 		·		-			
					-			
	 				-			
	 							
	<u> </u>							
	<u> </u>							
								
	ļ							
CONT	RACTOR'S	OR LANDOWNER'	S CERTIFICATIO	N: This water well wa	ıs 🛈 construc	ted, (2) recor	structed, or (3) plugged u	nder my jurisdiction and was
								nowledge and belief. Kansas
				This Water W				8.18.9
	business na	T	on Consultant			by (signatu	///	Maril
			n. PLEASE PRESS FIR	RMLY and PRINT clearly. Ple	ase fill in blanks		VII PI A	copies to Kansas Department
of Hea	ith and Environm	ent, Bureau of Water Pr	otection, Topeka, Kans	as 66620-7320. Telephone:	313-296-5514. Sen	d one to WATER	WELL OWNER and retain one for	your records.