			WATE	N WELL RECORD	LOLLI AAA	10-5 NSA 828	-1212				
1 LOCATION OF WATER WELL:			Fraction			Section Number	Township	Number	Range	Number	
County:	Sedgwic	<u>k</u>	SE 1/4	NE 1/4	SE 1/4	31	T	26 g	R 2	E)W	
				ddress of well if local			5089501	4			
250' S	W of the	Intersection of	32nd Street	North & Rock R	d., Wichi	ta, KS	Атосо М	0. 2316	MW-1		
2 WATE	R WELL OW	/NER: Groundwa	ater Managem	ment Section, Am	oco 011 C	ompany				ļ	
RR#, St.	Address, Bo	x # : 7201 E.	38th Street	, Space 7253			Board (of Agriculture, D	ivision of W	ater Resources	
City, State	, ZIP Code	: Tulsa, (OK 74145				Applica	tion Number:			
3 LOCAT	E WELL'S L	OCATION WITH 4	DEPTH OF C	OMPLETED WELL	21	ft. ELEVA	TION: Appr	ox. Surface	Elev: 13	90	
☐ AN "X"	IN SECTIO	N BOX:	enth(s) Ground	water Encountered	1 15.5	ft 2)	ft. 3.		.ft.	
т Г	1	100	ELL'S STATIC	WATER LEVEL	8.1	ft helow land sud	face measured	on mo/day/yr	02/16/8	9	
1	i										
. -	NW	NE	•	test data: Well wa				-		_	
1	!			'A., gpm: Well wa							
w F	<u> </u>			ter9in. to						i	
-				O BE USED AS:		,	8 Air condition	•	njection well	i	
1 .	SW	SE -X	1 Domestic	3 Feedlot		water supply	_		Other (Speci	• •	
1 1	1		2 Irrigation	4 Industrial		nd garden only d					
↓ L	ŀ	L Wi	as a chemical/b	acteriological sample	submitted t	o Department? Ye	sNo	.X; If yes,	mo/day/yr sa		
-		j mi	itted			Wat	ter Well Disinfe	ected? Yes	No	X	
5 TYPE	OF BLANK (CASING USED:		5 Wrought iron	8 Cc	ncrete tile	CASING	JOINTS: Glued	Cla	mped	
1 St		3 RMP (SR)		6 Asbestos-Cement	t 9 Ot	her (specify below	v)				
⊘ P\		4 ABS		7 Fiberglass							
Blank cas	ing diameter		to 6	ft., Dia	in	. to	ft., Dia	i	n. to	ft.	
Casing he	ight above la	and surface	. 2	in., weight		Ibs./f	ft. Wall thickne	ss or gauge No	Schedul	e 40	
		R PERFORATION N		-		≯vc ́		Asbestos-ceme		1	
1 St	eel	3 Stainless st	teel	5 Fiberglass	_	RMP (SR)	11	Other (specify)			
2 Br	ass	4 Galvanized	steel	6 Concrete tile		ABS		None used (ope			
		RATION OPENINGS			zed wrappe		8 Saw cut	• • •	11 None (c	pen hole)	
	ontinuous slo	_			wrapped	-	9 Drilled hole			,,,,,,	
	ouvered shut	•		7 Toro	• • •			ecify)			
		ED INTERVALS:	From	6 ft. to .		4 F					
SCHEEN-	FERFORATI	ED INTERVALS.									
	ODAVEL DA	OK INTERVALO:		ft. to	25	π., Fron	n)		
'	GHAVEL PA	CK INTERVALS:	From							π.	
al anaur	T 144TED141	4 111	From	ft. to		ft., Fron				π.	
_	T MATERIAL			Cement grout	<u>,</u>	entonite 4					
Grout Inte				ft., From	····						
		ource of possible cor				10 Livest	•		andoned wa		
	eptic tank	4 Lateral li					Fuel storage 15 Oil well/Gas well				
	ewer lines	5 Cess po	•			12 Fertiliz	12 Fertilizer storage 16 Other (specify below)				
3 W	atertight sew	er lines 6 Seepage	e pit	9 Feedyard			ticide storage				
	from well?	SSE					ny feet? 12				
FROM	то		LITHOLOGIC		FROM	и то		PLUGGING IN	ITERVALS		
0	4.5	Gray-Brown Lea		·							
4.5	8	Brown Lean to	Fat Silty C	lay							
8	14	Olive-Green Fa	at to Lean S	ilty Clay							
14	21.5	Fat Clay									
				1							

		-		and the second s							
							4				
								1.57			
			-								
	L		***************************************	0-100-07		L					
7 CONTI	RACTOR'S	OR LANDOWNER'S	CERTIFICATION	ON: This water well	was (Dcon	structed, (2) reco	nstructed, or (3) plugged und	er my jurisdi	ction and was	
	on (mo/day	02	2/15/89			. and this recor					
		's License No	416	This Water					3189		
		5 -100.100 110									
Under the	husiness na	me of Terraco	on Consultar			•		_ ///	ددرار		
	business na	ine oi	on Consultar			by (signat	ure)	Send top three &	duct	Department	

WATER WELL