


| | | | | | | | | | |
|--|--|--|--|-----------------------------|--|----------------------------------|--|---------------------------------|--|
| 1 LOCATION OF WATER WELL: Sedgwick | | FRACTION NE 1/4 NW 1/4 NE 1/4 | | Section Number 10 | | Township Number T 26 S | | Range Number R 2E E/W | |
| Distance and direction from nearest town or city street address of well if located within city? 12215 E. 69th N. Wichita, Kansas | | | | | | | | | |
| 2 WATER WELL OWNER: SCHNEIDER, Al | | Board of Agriculture, Division of Water Resource | | | | | | | |
| RR#, ST. ADDRESS, BOX #: 340 Shefford | | Application Number: | | | | | | | |
| CITY, STATE, ZIP CODE: Wichita, Kansas | | | | | | | | | |
| 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  | | 4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 01/24/1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 90 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No | | | | | | | |
| 5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing Diameter 5 in. to 30 ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs./ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped SCREEN-PERFORATION INTERVALS: from 30 ft. to 90 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 24 ft. to 90 ft., From ft. to ft. | | CASING JOINTS: Glued X Clamped Welded Threaded SDR-26 Wall thickness or gauge No. .214 7 PVC 10 Asbestos-cement 8 RMP (SR) 11 other (specify) 8 Saw cut 12 None used (open hole) 9 Drilled holes 10 Other (specify) | | | | | | | |
| 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) None Apparent Direction from well? How many feet? | | | | | | | | | |
| FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS | | | | | | | | | |
| 0 3 topsoil | | | | | | | | | |
| 3 19 clay | | SEPTIC SYSTEM NOT | | | | | | | |
| 19 39 brown shale | | INSTALLED AT THIS TIME | | | | | | | |
| 39 90 grey shale | | | | | | | | | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/24/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 01/27/95 Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick | | | | | | | | | |