

1 LOCATION OF WATER WELL:

FRACTION

Butler

SE

1/4

NE

1/4

SE

1/4

Section Number

Township Number

Range Number

T 26 S

R 3

E/W

Distance and direction from nearest town or city street address of well if located within city?

5703 S. West Prairie Creek

Benton, Kansas


WATER WELL OWNER: ROUNDS, Betty

RR#, ST. ADDRESS, BOX #: 5703 S. West Prairie Creek

CITY, STATE, ZIP CODE: Benton, Kansas

Board of Agriculture, Division of Water Resource

Application Number:

LOCATE WELL'S LOCATION WITH
AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 125 ft. ELEVATION:

Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.

06/20/1996

WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 12 in. to 125 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)

5 Wrought iron

8 Concrete tile

CASING JOINTS:

Glued X Clamped

2 PVC 4 ABS

6 Asbestos-Cement

9 Other (Specify below)

Welded

7 Fiberglass

SDR-26

Threaded

Blank casing Diameter 5 in. to 24

ft., Dia

in. to

ft., Dia

in. to

ft.

Casing height above land surface 12 in., weight 2.35 lbs./ft.

ft. ,

lbs./ft.

.214

TYPE OF SCREEN OR PERFORATION MATERIAL:

Wall thickness or gauge No.

10 Asbestos-cement

1 Steel 3 Stainless Steel

5 Fiberglass

7 PVC

11 other (specify)

2 Brass 4 Galvanized steel

6 Concrete tile

8 RMP (SR)

12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

1 Continuous slot 3 Mill slot

6 Wire wrapped

9 Drilled holes

2 Louvered shutter 4 Key punched

7 Torch cut

10 Other (specify)

SCREEN-PERFORATION INTERVALS:

from 24

ft. to 125

ft., From

ft. to

ft.

from

ft. to

ft., From

ft. to

ft.

GRAVEL PACK INTERVALS:

from 24

ft. to 125

ft., From

ft. to

ft.

from

ft. to

ft., From

ft. to

ft.

6 GROUT MATERIAL: 1 Neat cement

2 Cement grout

3 Bentonite

4 Other

bentonite hole plug

Grout Intervals: From 4 ft. to 24

ft. From

ft. to

ft. From

ft. to

What is the nearest source of possible contamination:

- 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well
- 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
- 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

None Apparent

How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 4 topsoil

4 10 clay

10 12 sand

12 18 clay

18 125 shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06/20/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 06/21/96.

Under the business name of Harp Well & Pump Service, Inc. by (signature)

Todd S. Harp