

1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number	
Butler	NE	1/4	NE	1/4	NW	1/4	
Distance and direction from nearest town or city street address of well if located within city?							
16803 SW Parallel St. Benton, Kansas							
WATER WELL OWNER:	LYON, Truman			Board of Agriculture, Division of Water Resource			
RR#, ST. ADDRESS, BOX #:	16917 SW Parallel St.			Application Number:			
CITY, STATE, ZIP CODE:	Benton, Kansas						
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 67 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 27 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 02/03/1997 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 67 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5	TYPE OF CASING USED:					CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped	
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	9 Other (Specify below)	Welded		
2 PVC	4 ABS	6 Asbestos-Cement	7 Fiberglass	SDR-26	Threaded		
Blank casing Diameter 5 in. to 25	ft., Dia	in. to	ft., Dia	in. to	ft.		
Casing height above land surface 12 in.,	weight 2.35	lbs. / ft.	7 PVC	Wall thickness or gauge No. 10 Asbestos-cement	.214		
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 other (specify)			
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:							
1 Continous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)			
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes				
7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVALS: from 25 ft. to 67 ft., From ft. to ft.							
from ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: from 24 ft. to 67 ft., From ft. to ft.							
from ft. to ft., From ft. to ft.							
6	GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
13 Insecticide storage None Apparent How many feet?							
Direction from well?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	2	topsoil					
2	20	clay					
20	67	shale					
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and						

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/03/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 02/04/97. Under the business name of Harp Well & Pump Service, Inc. by (signature) Franklin S. Harp

Todd S. Harp