

1 LOCATION OF WATER WELL:

FRACTION

Section Number

Township Number

Range Number

Butler

NE 1/4

NE 1/4

SE 1/4

36

T 26 S

R 3E E/W

Distance and direction from nearest town or city street address of well if located within city?

2 m. W. &amp; 3 1/2 S of Towanda Kansas


WATER WELL OWNER: TRENARY, Jerry

RR#, ST. ADDRESS, BOX #: 11120 SW 56th Terrace

Board of Agriculture, Division of Water Resource

CITY, STATE, ZIP CODE: Towanda, Kansas

Application Number:

LOCATE WELL'S LOCATION WITH  
AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 127 ft. ELEVATION:

Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 02/04/1997

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 12 in. to 127 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No  ; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes  No 

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)

5 Wrought iron

8 Concrete tile

CASING JOINTS:

Glued  Clamped

2 PVC 4 ABS

6 Asbestos-Cement

9 Other (Specify below)

Welded

7 Fiberglass

SDR-26

Threaded

Blank casing Diameter 5 in. to 40

ft., Dia

in. to

ft., Dia

in. to

ft.

Casing height above land surface 12 in., weight 2.35 lbs./ft.

Wall thickness or gauge No.

.214

TYPE OF SCREEN OR PERFORATION MATERIAL:

7 PVC

10 Asbestos-cement

1 Steel 3 Stainless Steel

5 Fiberglass

8 RMP (SR)

11 other (specify)

2 Brass 4 Galvanized steel

6 Concrete tile

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

1 Continous slot 3 Mill slot

6 Wire wrapped

9 Drilled holes

2 Louvered shutter 4 Key punched

7 Torch cut

10 Other (specify)

SCREEN-PERFORATION INTERVALS: from 40 ft. to 127 ft., From ft. to ft.

from ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: from 24 ft. to 127 ft., From ft. to ft.

from ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug

Grout Intervals: From 4 ft. to 24 ft. ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

10 Livestock pens 14 Abandon water well

1 Septic tank 4 Lateral lines

7 Pit privy

11 Fuel storage

2 Sewer lines 5 Cess pool

8 Sewage lagoon

12 Fertilizer storage

3 Watertight sewer lines 6 Seepage pit

9 Feedyard

13 Insecticide storage

Direction from well? North How many feet? 120

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 4 topsoil

4 65 rock

65 120 shale

120 129 rock

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/04/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236. This Water Well Record was completed on (mo/day/yr) 02/06/97.

Under the business name of Harp Well &amp; Pump Service, Inc. by (signature)

Todd S. Harp