


1 LOCATION OF WATER WELL:	Fraction County: Butler	NE $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 21	Township Number T 26 S	Range Number R 3 E		
Distance and direction from nearest town or city street address of well if located within city? 3030 SW Rustic Rd., Benton, KS							
2 WATER WELL OWNER:	Kevin Jones 3030 SW Rustic Rd. Benton, KS 67017		Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 70 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 4/27/00 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 10 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED:	1 Steel <input checked="" type="checkbox"/> 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued X Clamped Welded Threaded		
Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. SDR26							
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)		
SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 20 ft. to 70 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 4 ft. to 20 ft., From ft. to ft., From ft. to ft.	2 Cement grout	3 Bentonite	4 Other				
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)		
Direction from well?	How many feet?						
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	10	Clay					
10	23	Lime					
23	38	Shale					
38	58	Lime and Shale					
58	70	Cherty Lime					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, <input type="checkbox"/> reconstructed, or <input type="checkbox"/> plugged under my jurisdiction and was completed on (mo/day/year) 4/27/00, and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 171. This Water Well Record was completed on (mo/day/year) 4/30/00, under the business name of G&S Drilling, Inc.						by (signature)	