

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>		<u>SW</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$	<u>4</u>	T <u>26</u> S	R <u>3E</u> E/W
Distance and direction from nearest town or city street address of well if located within city? <u>305 Wichita St, Benton, KS</u>					
2 WATER WELL OWNER: <u>Tim Smith</u>					
RR#, St. Address, Box # : <u>305 Wichita St</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : <u>Benton, KS 67017</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>8.0</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>9</u> in. to <u>8.0</u> ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
② PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter <u>5</u> in. to <u>6.0</u> ft., Dia			7 Fiberglass		Threaded
Casing height above land surface <u>12</u> in., weight					
TYPE OF SCREEN OR PERFORATION MATERIAL:		⑦ PVC 10 Asbestos-cement			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot		③ Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From <u>6.0</u> ft. to <u>8.0</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>2.0</u> ft. to <u>8.0</u> ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ③ Bentonite 4 Other					
Grout Intervals: From <u>4</u> ft. to <u>2.0</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	22	clay			
22	32	shale			
32	36	lime			
36	48	shale			
48	66	lime w/ shale str			
66	80	clayey lime			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-11-00</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>171</u> This Water Well Record was completed on (mo/day/yr) <u>9-15-00</u> under the business name of <u>GXS Drilling Inc</u> by (signature) <u>[Signature]</u>					