

1 LOCATION OF WATER WELL:	Fraction County: <i>Butler</i>	SW $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 8	Township Number T 26 S	Range Number R 3 E
Distance and direction from nearest town or city street address of well if located within city? <i>1 1/4 mi NW of Benton KS</i>					
2 WATER WELL OWNER:	<i>FRUTION LLC.</i>				
RR#, St. Address, Box #	4911 S Meridan				
City, State, ZIP Code	Wichita KS 67217				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
4 DEPTH OF COMPLETED WELL	125 ft. ELEVATION:				
Depth(s) Groundwater Encountered	1	63	ft. 2	97	ft. 3
WELL'S STATIC WATER LEVEL	ft. below land surface measured on mo/day/yr				
Pump test data: Well water was	ft. after hours pumping gpm				
Est. Yield	25	gpm: Well water was	ft. after hours pumping gpm		
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well		
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering		
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)	10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/ys sample was submitted					
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>					
5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped		
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded		
2 PVC	7 Fiberglass		Threaded		
Blank casing diameter	5 in. to 60	ft., Dia 80	in. to 85	ft., Dia	in. to ft.
Casing height above land surface	18	in., weight	50R26	160	lbs./ft. Wall thickness or guage No. 50R26
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-Cement			
1 Steel	3 Stainless Steel	11 Other (Specify)			
2 Brass	4 Galvanized Steel	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)		
1 Continuous slot	6 Wire wrapped	9 Drilled holes			
2 Louvered shutter	7 Torch cut	10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From	60	ft. to 80	ft., From	105	ft. to 125 ft.
From	80	ft. to 125	ft., From		ft. to
GRAVEL PACK INTERVALS: From	85	ft. to 125	ft., From		ft. to
From		ft. to	ft., From		ft. to
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From	85	ft. to 95	ft., From 0	ft. to 23	ft., From
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well			
1 Septic tank	7 Pit privy	11 Fuel storage			
2 Sewer lines	8 Sewage lagoon	12 Fertilizer storage			
3 Watertight sewer lines	9 Feedyard	13 Insecticide storage			
6 Seepage pit		How many feet? 125			
Direction from well? E					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	47	Brown Clay			
47	63	Light Gray Clay			
63	64	Brown Lime			
64	97	GRAY Shale			
97	125	Shale w/ Lime streaks			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>5-17-04</i> and this record is true to the best of my knowledge and belief. Kansas				
Water Well Contractor's Licence No	444 This Water Well Record was completed on (mo/day/yr) <i>5-17-04</i>				
under the business name of	by (signature) <i>John D. Thompson</i>				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each completed well.					