


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SW 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city?							
1002 Rosemont Andover, Kansas							
2 WATER WELL OWNER: WOMACK HOMES	Board of Agriculture, Division of Water Resource						
RR#, ST. ADDRESS, BOX #: 14200 W. Onewood Place #13	Application Number:						
CITY, STATE: Wichita, Kansas							
ZIP CODE: 67235							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 97 ft.	ELEVATION: ft. ft. ft.					
Depth of groundwater Encountered: ft. ft. ft.							
WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/28/09							
Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm							
Bore Hole Diameter 12 in. to 97 ft. and in. to ft.							
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO							
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 6. Asbestos-Cement	7. Fiberglass 8. Concrete tile	9. Other (Specify below) SDR-26	CASING JOINTS: Glued Threaded Welded Clamped			
Blank casing diameter 5 in.	to 37 ft.	Dia.	in. to ft.	Dia. in. to ft.			
Casing height above land surface: 12 in.,		Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 9. ABS 10. Asbestos-Cement 11. Other (specify) 12. None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)							
SCREEN - PERFORATION INTERVAL From 37 ft. to 97 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft., From ft. to ft.							
6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft.	1. Neat cement 2. Cement Grout 3. Bentonite	Other	bentonite hole plug				
What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line	4. Lateral lines 5. Cess Pool 6. Seepage pit	7. Pit privy 8. Sewage lagoon 9. Feed yard	10. Livestock pens 11. Fuel storage 12. Fertilizer storage	13. Insecticide storage 14. Abandon water well 15. Oil well/Gas well 16. Other (specify below)			
Direction from well?: South	How many feet? 10 ft. plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	4	topsoil					
4	15	clay					
15	80	shale					
80	97	shale and limestone					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 7/28/2009 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 7/29/2009						
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp						