

1 LOCATION OF WATER WELL:		Fraction <u>NW</u>	Section Number <u>24 23</u>	Township Number <u>T 26 S</u>	Range Number <u>R 3E EW</u>
County: <u>Butler</u>					
Distance and direction from nearest town or city street address of well if located within city? <u>12457 SW 30th St.</u>					
2 WATER WELL OWNER:		<u>Lawrence Bessent</u> <u>Justin Kaelzel (new owner)</u>			
Rte, St. Address, Box # :		<u>12457 SW 30th St.</u>			
City, State, ZIP Code :		<u>Benton, KS 67017</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>116</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>9</u> in. to <u>116</u> ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
② PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
		7 Fiberglass Threaded			
Blank casing diameter <u>5</u> in. to <u>76</u> ft. Dia		Blank casing diameter in. to ft. Dia			
Casing height above land surface <u>12</u> in. weight		Casing height above land surface in. weight lbs/ft. Wall thickness or gauge No. <u>SDR26</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		⑦ PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot ③ Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN PERFORATED INTERVALS:		From <u>76</u> ft. to <u>116</u> ft. From ft. to ft.			
		From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>20</u> ft. to <u>116</u> ft. From ft. to ft.			
		From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		③ Bentonite 4 Other			
1 Neat cement 2 Cement grout					
Grout intervals: From <u>4</u> ft. to <u>20</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	26	Clay			
26	48	Shale			
48	55	Lime			
55	110	Shale w/lime stks			
110	116	Lime (fractured)			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION. This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6/10/99</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>171</u> This Water Well Record was completed on (mo/day/yr) <u>7/2/99</u> under the business name of <u>G & S Drilling, Inc.</u> by (signature) <u>[Signature]</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC

N

N

2