

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction County: <i>Butler</i>	Section Number 5	Township Number T 26 S	Range Number R 3 E		
Distance and direction from nearest town or city street address of well if located within city? <i>Appoxy 5 mi N. of Andover</i>						
2 WATER WELL OWNER:	<i>Coastal Derby Refining</i>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #	202 W. 1st Wichita KS		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:						
4 DEPTH OF COMPLETED WELL	28	ft. ELEVATION:				
Depth(s) Groundwater Encountered	1.	ft. 2.	ft. 3.	ft.		
WELL'S STATIC WATER LEVEL	23	ft. below land surface measured on mo/day/yr				
Pump test data: Well water was	ft. after	hours pumping	gpm			
Est. Yield	gpm	ft. after	hours pumping	gpm		
Bore Hole Diameter	8	in. to	28	ft., and in. to ft.		
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well			
1 Domestic	3 Feedlot	6 Oil field water supply	12 Other (Specify below)			
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED:	1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
	2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	
			7 Fiberglass		Threaded	
Blank casing diameter	4	in. to	28	ft., Dia	in. to	ft., Dia
Casing height above land surface	30	in., weight			lbs./ft.	Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	10 Other (specify)		
SCREEN-PERFORATED INTERVALS:	From	18	ft. to	28	ft., From	ft. to
GRAVEL PACK INTERVALS:	From	17	ft. to	28	ft., From	ft. to
From		ft. to		ft., From	ft. to	ft.
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:	From	17	ft. to	17	ft., From	ft. to
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well		
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
How many feet? <i>1/4 MILE</i>						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	25	SILTY CLAY w/ L.S.				
25	28	SHALE				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>10/4/81</i> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <i>102</i> This Water Well Record was completed on (mo/day/year) <i>10/31/81</i> under the business name of <i>Payne Western</i> Wichita by (signature) <i>J. M. Payne</i>						

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.