


## WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: <i>Butler</i>	NE $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 5	Township Number T 26 S	Range Number R 3 EW
Distance and direction from nearest town or city street address of well if located within city? <i>Approx 5 mi N. of Andover</i> MW -40						
2 WATER WELL OWNER:		<i>Coastal Derby Refining</i>		Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #:		202 W 1st Wichita KS		Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 37 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 8 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 37 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:		1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded Threaded
Blank casing diameter		4 in. to 27 ft.	Dia	in. to ft. Dia	in. to ft.	
Casing height above land surface		30 in.	weight	lbs./ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 2 Brass		3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 27 ft.	to 37 ft.	From ft.	to ft.	
GRAVEL PACK INTERVALS:		From 26 ft.	to 37 ft.	From ft.	to ft.	
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals:		From 0 ft. to 26 ft.	ft.	ft. to ft.	ft. to ft.	
What is the nearest source of possible contamination:						
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well?		How many feet? <i>1/4 MILE</i>				
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	25	<i>SILTY CLAY</i>				
25	35	<i>SILTY CLAY w/ LIME STONE</i>				
35	37	<i>SHALE</i>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>10/4/91</i> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <i>102</i> This Water Well Record was completed on (mo/day/year) <i>10/31/91</i> under the business name of <i>Payne Western</i> <i>Wichita</i> by (signature) <i>R. P. Moyer</i>						